



CHG: MAG VAR, MSA, MHA, all RTE

RNAV STAR RWY 01

ATPEL 4A BAPTU 4A EMDUR 4A GIDKI 4A NESUK 3A VAXUN 2A

DME/DME OPS: NOT SUPPORTED

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES

WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC

CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR

RCF: SELECT TRANSPONDER CODE 7600

RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: FOLLOW THE
STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND

EFKK RNAV STAR RWY 01										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ATPEL 4A RNAV 1	010	IF	ATPEL	-	-	-	-	F100+		
	020	TF	RUDED	-	033°	044.2°T	13.5	A2400+		K240-
	030	TF	UNPOD	-	090°	100.4°T	5.0	A2400+		

BAPTU 4A RNAV 1	010	IF	BAPTU	-	-	-	-	F100+		
	020	TF	UNPOD	-	359°	010.0°T	15.9	A2400+		

EMDUR 4A RNAV 1	010	IF	EMDUR	-	-	-	-	F100+		
	020	TF	AKOSE	-	201°	212.0°T	8.9			
	030	TF	XUGDI	-	180°	190.9°T	10.1			
	040	TF	SOGBU	-	180°	190.8°T	10.7	A2400+		K240-
	050	TF	UNPOD	-	270°	280.7°T	5.0	A2400+		

GIDKI 4A RNAV 1	010	IF	GIDKI	-	-	-	-	F100+		
	020	TF	UNPOD	-	331°	342.4°T	16.2	A2400+		

NESUK 3A RNAV 1	010	IF	NESUK	-	-	-	-	F100+		
	020	TF	RUDED	-	129°	139.5°T	14.3	A2400+		K240-
	030	TF	UNPOD	-	090°	100.4°T	5.0	A2400+		

VAXUN 2A RNAV 1	010	IF	VAXUN	-	-	-	-	F100+		
	020	TF	AKOSE	-	218°	229.4°T	10.7			
	030	TF	XUGDI	-	180°	190.9°T	10.1			
	040	TF	SOGBU	-	180°	190.8°T	10.7	A2400+		K240-
	050	TF	UNPOD	-	270°	280.7°T	5.0	A2400+		

RNAV Holdings							
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM
UNPOD	010.6°T	000°	Left	K230-	A2400	1 MIN	-

WPT COORD
SEE PAGE EFKK AD 2.15 - 1