

MUENCHEN
RNP RWY 08R

INSTRUMENT APPROACH PROCEDURE
TABULAR DESCRIPTION

Procedure Remarks

1. WHEN RWY VACATED, CONTACT GROUND.
2. * OPERATIONAL FL.
3. BARO-VNAV OPERATIONS NOT AUTHORIZED BELOW -15°C.
4. EGNOS CHANNEL 42249 E08B

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from OTT	IF	OTT	N 48 10 49.40 E 011 48 59.50	-	-	-	-	A5000+	-	-	RNP APCH	-
	TF	DM451	N 48 13 17.41 E 011 20 44.28	-	(T277.6) 275	19.1	-	-	-	-	RNP APCH	-
	TF	DM441	N 48 18 26.45 E 011 19 48.03	-	(T353.1) 350	5.2	-	-	-	-	RNP APCH	-
APCH	TF	BEGEN	N 48 19 10.32 E 011 28 53.40	-	(T083.1) 080	6.1	-	A5000+	-	-	RNP APCH	-
	TF	RW08R	N 48 20 26.41 E 011 45 03.66	Y	(T083.2) 080	10.9	-	-	-	-3.00 / 50	RNP APCH	-
Missed APCH	CF	DM561	N 48 20 40.66 E 011 48 08.67	Y	(T083.4) 080	2.1	-	-	-	-	RNP APCH	-
	CA	-	-	-	(T083.4) 080	-	-	A1900+	-	-	RNP APCH	-
	DF	OTT	N 48 10 49.40 E 011 48 59.50	-	-	-	R	@A5000	-	-	RNP APCH	-

RNAV HOLDING IDENTIFICATION

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	OTT	N 48 10 49.40 E 011 48 59.50	(T083.1) 080	230-	A5000+	1 min	R	-