

KARLSRUHE/BADEN-BADEN
RWY 03/21

STANDARD INSTRUMENT ARRIVAL (STAR)
TABULAR DESCRIPTION
RNAV(GPS)

KARLSRUHE ONE LIMA KRH 1L											
1. KRH is IAF RWY21 and by ATC only. 2. Operational altitude 6500ft during activity of NLFS.											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	KRH	N 48 59 34.60 E 008 35 03.25	-	-	-	-	A6000+	-	-	refer to chart	-
TF	KBA	N 48 47 52.68 E 008 05 51.19	-	(T238.9) 237	22.5	-	A6000+	-	-	refer to chart	-

LADAT ONE LIMA LADAT 1L											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	LADAT	N 49 15 54.92 E 007 50 22.10	-	-	-	-	A6000+	-	-	refer to chart	-
TF	ABKUT	N 48 59 00.00 E 008 15 00.00	-	(T136.1) 134	23.4	-	-	-	-	refer to chart	-
TF	KBA	N 48 47 52.68 E 008 05 51.19	-	(T208.5) 207	12.7	-	A6000+	-	-	refer to chart	-

SULZ ONE LIMA SUL 1L											
Operational altitude 6500ft during activity of NLFS.											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
IF	SUL	N 48 22 53.71 E 008 38 41.41	-	-	-	-	A6000+	-	-	refer to chart	-
TF	KBA	N 48 47 52.68 E 008 05 51.19	-	(T319.1) 317	33.1	-	A6000+	-	-	refer to chart	-

RNAV HOLDING IDENTIFICATION									
Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) Mag Track°	Outbound Time (min)/ Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Remarks	
HM	KBA	N 48 47 52.68 E 008 05 51.19	(T032.0) 030	1 MIN	R	A6000+ / FL110-	230-	-	