

STAR RNAV 1 RWY32 description

NEVNI 3T (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	NEVNI	-	-	-	-	-	-	-	RNAV1
TF	P0402	-	185°(188.1°)	-	20.3	-	+FL110	-	RNAV1
TF	DREUX	-	185°(188.1°)	-	3.9	-	+6000	-230	RNAV1
TF	ADSAS	-	128°(131.4°)	-	5.0	-	+5000 (3)	-210	RNAV1

NEVNI 3W

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	NEVNI	-	-	-	-	-	-	-	RNAV1
TF	P0404	-	147°(150.6°)	-	9.4	-	+FL110	-	RNAV1
TF	P0401	-	147°(150.6°)	-	5.0	-	+6000	-230	RNAV1
TF	UPGAV	-	148°(150.6°)	-	6.0	-	+5000 (3)	-210	RNAV1

OSBUL 2A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OSBUL	-	-	-	-	-	-	-	RNAV1
TF	LAISH	-	347°(350.4°)	-	13.4		+6000	-	RNAV1
TF	ADSAS	-	038°(041.4°)	-	12.2		+5000 (3)	-210	RNAV1

OSTEG 3T

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	OSTEG	-	-	-	-	-	-	-	RNAV1
TF	AIXBA	-	298°(300.8°)	-	5.2	-	+6000	-	RNAV1
TF	UVNON	-	298°(300.8°)	-	7.0	-	+6000	-	RNAV1
TF	INFRI	-	223°(225.7°)	-	4.1	-	+5000 (3)	-	RNAV1
TF	PO403	-	223°(225.7°)	-	6.5	-	+5000 (3)	-210	RNAV1
TF	ELDIP		312°(315.2°)	-	5.0	-	+5000 (3)	-210	RNAV1

PIRWO 3A (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	PIRWO	-	-	-	-	-	-	-	RNAV1
TF	XENRU	-	151°(154.2°)	-	13.1	-	+FL110	-	RNAV1
TF	UVNON	-	223°(225.7°)	-	7.1	-	+6000	-	RNAV1
TF	INFRI	-	223°(225.7°)	-	4.1	-	+5000 (3)	-	RNAV1
TF	PO403	-	223°(225.7°)	-	6.5	-	+5000 (3)	-210	RNAV1
TF	ELDIP	-	312°(315.2°)	-	5.0	-	+5000 (3)	-210	RNAV1

TAFIQ 2A

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TAFIQ	-	-	-	-	-	-	-	RNAV1
TF	P0406	-	215°(218.2°)	-	6.4	-	+FL110	-	RNAV1
TF	P0401	-	215°(218.2°)	-	3.0	-	+6000	-230	RNAV1
TF	UPGAV	-	148°(150.6°)	-	6.0	-	+5000 (3)	-210	RNAV1

TAFIQ 2B (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TAFIQ	-	-	-	-	-	-	-	RNAV1
TF	P0406	-	215°(218.2°)	-	6.4	-	+FL110	-	RNAV1
TF	P0401	-	215°(218.2°)	-	3.0	-	+6000	-230	RNAV1
TF	P0402	-	230°(232.8°)	-	12.5	-	+6000	-230	RNAV1
TF	DREUX	-	185°(188.0°)	-	3.9	-	+6000	-230	RNAV1
TF	ADSAS	-	128°(131.4°)	-	5.0	-	+5000 (3)	-210	RNAV1

TZO 2T

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TZO	-	-	-	-	-	-	-	RNAV1
TF	EKDOG	-	112°(115.1°)	-	23.0	-	+FL110	-	RNAV1
TF	DIRVU	-	112°(115.1°)	-	11.1	-	+6000	-	RNAV1
TF	DREUX	-	128°(131.4°)	-	6.0	-	+6000	-230	RNAV1
TF	ADSAS	-	128°(131.4°)	-	5.0	-	+5000 (3)	-210	RNAV1

XUBKA 2B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XUBKA	-	-	-	-	-	-	-	RNAV1
TF	DIGTO	-	343°(346.4°)	-	13.5	-	+6000	-	RNAV1
TF	INFRI	-	298°(300.8°)	-	13.2	-	+6000	-	RNAV1
TF	PO403	-	223°(225.7°)	-	6.5	-	+5000 (3)	-210	RNAV1
TF	ELDIP		312° (315.2)	-	5.0		+5000 (3)	-210	RNAV1

HOLDING RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	ELDIP	312°(315.2°)	4.0	- / 5.1	L	5000 (4)	5000 (5)	-210	3° E	RNAV1
HM	UPGAV	133°(136.0°)	4.0	- / 5.1	L	5000 (4)	-	-210	3° E	RNAV1
HM	ADSAS	128°(131.4°)	4.0	- / 5.1	R	5000 (4)	-	-210	3° E	RNAV1

REMARKS

- (1) for RNAV system with holding functionality
- (2) for RNAV system without holding functionality
- (3) MEA 3000FT ATC Discretion
- (4) MHA 4000FT ATC Discretion
- (5) Higher Altitudes or Levels ATC Discretion

WAYPOINT LIST

Waypoint Identifier	Coordinates
PO401	45° 26' 24.40" N 010° 35' 23.18" E
PO402	45° 18' 50.55" N 010° 21' 18.85" E
PO403	45° 09' 29.70" N 010° 42' 48.51" E
PO404	45° 30' 45.78" N 010° 31' 53.85" E
PO406	45° 28' 46.25" N 010° 38' 00.66" E