

Procedure Remarks

STANDARD INSTRUMENT APPROACH FROM IAF ERF AND IAF DE430 NOT TO BE USED DURING ACTIVITY OF NLFS (ED-R 150).

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from DE430	IF	DE430	N 51 00 29.85 E 010 35 39.95	N	-	-	-	A4000+	-	-	RNP APCH	-
	TF	BULEM	N 51 00 00.73 E 010 41 57.40	N	(T 096.9) 094	4.0	-	A4000+	-	-	RNP APCH	-
Initial APCH from ERF	IF	ERF	N 50 57 03.13 E 011 14 12.07	N	-	-	-	A5000+	-	-	RNP APCH	-
	TF	DE422	N 51 04 28.82 E 010 49 13.43	N	(T 295.4) 293	17.4	-	-	-	-	RNP APCH	-
	TF	DE421	N 51 04 58.34 E 010 42 55.49	N	(T 277.1) 274	4.0	-	-	-	-	RNP APCH	-
	TF	DE420	N 51 05 27.51 E 010 36 37.41	N	(T 277.0) 274	4.0	-	A5000+	-	-	RNP APCH	-
	TF	DE430	N 51 00 29.85 E 010 35 39.95	N	(T 186.9) 184	5.0	-	A4000+	220-	-	RNP APCH	-
	TF	BULEM	N 51 00 00.73 E 010 41 57.40	N	(T 096.9) 094	4.0	-	A4000+	-	-	RNP APCH	-
APCH	TF	RW09	N 50 58 52.60 E 010 56 23.04	Y	(T 097.0) 094	9.2	-	-	-	-3.0/50	RNP APCH	-
Missed APCH	VA	-	-	-	(T 097.0) 094	-	-	A1500+	-	-	RNP APCH	-
	CF	ERF	N 50 57 03.13 E 011 14 12.07	N	(T 099.4) 096	-	R	-	-	-	RNP APCH	-
	TF	DE437	N 50 56 47.70 E 011 21 52.18	Y	(T 093.0) 090	4.9	-	-	230-	-	RNP APCH	-
	DF	ERF	N 50 57 03.13 E 011 14 12.07	N	-	-	L	@ A5000	-	-	RNP APCH	-

RNAV HOLDING IDENTIFICATION								
Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) Mag Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time (MIN) / Distance outbound	Turn Direction	Remarks
HM	ERF	N 50 57 03.13 E 011 14 12.07	(T 007.2) 004	230-	A5000+	1	L	-