

**STANDARD ARRIVAL CHART –  
INSTRUMENT (STAR) - ICAO**

**RIYADH / King Khaled Intl (OERK)  
RNAV RWY 15L/15R**

UKIVU 1A ASNUM 1A MEPDA 1A ALTIT 1A  
SEPDO 1A DEBUD 1A ESRAT 2A

**TABULAR DESCRIPTION**

RNAV RWY 15L/15R										
Serial Number	Path Description	Waypoint Identifier	Fly Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude	Speed Limit (NM/h)	Navigation Specification
<b>UKIVU 1A ARRIVAL</b>										
010	IF	UKIVU	-	-	-	-	-	-FL240 +FL160	-	RNAV 1
020	TF	ETBAS	-	280 (283.5)	-3.3	23.8	-	-FL190 +FL160	-	RNAV 1
030	TF	RK719	-	248 (251.2)	-3.3	20.8	-	-12000	-	RNAV 1
040	TF	RK712	-	248 (251.1)	-3.3	9.9	-	-	-	RNAV 1
050	TF	RK705	-	236 (238.9)	-3.3	7.0	-	-	-	RNAV 1
060	TF	RK797	-	236 (238.9)	-3.3	7.0	-	+6000	-	RNAV 1
070	TF	SISIR	-	147 (150.1)	-3.3	7.0	-	+6000	-	RNAV 1
080	TF	RK783	-	147 (150.1)	-3.3	7.0	-	+6000	-230	RNAV 1
090	TF	RK776	-	237 (240.1)	-3.3	7.0	-	+6000	-230	RNAV 1
100	TF	RK769	-	327 (330.1)	-3.3	7.0	-	+6000	-230	RNAV 1
110	TF	RK762	-	327 (330.1)	-3.3	7.0	-	+6000	-230	RNAV 1
120	TF	RK755	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
130	TF	RK748	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
140	TF	RK741	-	327 (330.0)	-3.3	7.0	-	+6000	-210	RNAV 1
150	TF	RK734	-	236 (239.4)	-3.3	7.0	-	+6000	-210	RNAV 1
160	TF	RK727	-	146 (149.9)	-3.3	7.0	-	+6000	-210	RNAV 1
170	TF	RK721	-	147 (149.9)	-3.3	7.0	-	+6000	-210	RNAV 1

ASNUM 1A ARRIVAL										
Serial Number	Path Description	Waypoint Identifier	Fly Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude	Speed Limit (NM/h)	Navigation Specification
010	IF	ASNUM	-	-	-	-	-	+FL220 +FL160	-	RNAV 1
020	TF	ETBAS	-	223 (226.4)	-3.3	7.8	-	-FL190 +FL160	-	RNAV 1
030	TF	RK719	-	248 (251.2)	-3.3	20.8	-	-12000	-	RNAV 1
040	TF	RK712	-	248 (251.1)	-3.3	9.9	-	-	-	RNAV 1
050	TF	RK705	-	236 (238.9)	-3.3	7.0	-	-	-	RNAV 1
060	TF	RK797	-	236 (238.9)	-3.3	7.0	-	+6000	-	RNAV 1
070	TF	SISIR	-	147 (150.1)	-3.3	7.0	-	+6000	-	RNAV 1
080	TF	RK783	-	147 (150.1)	-3.3	7.0	-	+6000	-230	RNAV 1
090	TF	RK776	-	237 (240.1)	-3.3	7.0	-	+6000	-230	RNAV 1
100	TF	RK769	-	327 (330.1)	-3.3	7.0	-	+6000	-230	RNAV 1
110	TF	RK762	-	327 (330.1)	-3.3	7.0	-	+6000	-230	RNAV 1
120	TF	RK755	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
130	TF	RK748	-	327 (330.0)	-3.3	7.0	-	+6000	-230	RNAV 1
140	TF	RK741	-	327 (330.0)	-3.3	7.0	-	+6000	-210	RNAV 1
150	TF	RK734	-	236 (239.4)	-3.3	7.0	-	+6000	-210	RNAV 1
160	TF	RK727	-	146 (149.9)	-3.3	7.0	-	+6000	-210	RNAV 1
170	TF	RK721	-	147 (149.9)	-3.3	7.0	-	+6000	-210	RNAV 1

MEPDA 1A ARRIVAL										
Serial Number	Path Description	Waypoint Identifier	Fly Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude	Speed Limit (NM/h)	Navigation Specification
010	IF	MEPDA	-	-	-	-	-	-FL260 +FL160	-	RNAV 1
020	TF	KOBOX	-	261 (263.8)	-3.3	18.1	-	-FL240 +FL160	-	RNAV 1
030	TF	RK750	-	298 (301.0)	-3.3	9.4	-	-12000	-	RNAV 1
040	TF	RK719	-	298 (301.0)	-3.3	31.0	-	-12000	-	RNAV 1
050	TF	RK712	-	248 (251.1)	-3.3	9.9	-	-	-	RNAV 1

CHANGE: NEW TABLE

Amdt: Original, 28 Nov 24

ICAO PANS OPS