

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
26	LIH Sequence flash available	G LIH	3.0°	W LIH	-	THR – 794 m: W LIH 855 – 1232 m: Y LIH; 60 m apart	R LIH	-

Remarks	
	10
08	Nil
26	Nil

**EDHK AD 2.15 Other lighting, secondary power supply**

1	ABN/IBN location, characteristics and hours of operation	ABN white/white
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDHK 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL
4	Secondary power supply including switch-over time	Available
5	Remarks	Nil

**EDHK AD 2.16 Helicopter landing area**

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	Not specified, according to directions from TWR

**EDHK AD 2.17 ATS airspace**

1	Designation and lateral limits	RMZ
2	Vertical limits	1000 ft AGL
3	Airspace classification	G
4	ATS unit call sign Language(s)	KIEL INFORMATION English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.2