

AUGSBURG
RWY 25

INSTRUMENT APPROACH PROCEDURE
TABULAR DESCRIPTION
RNP

Procedure Remarks

- 1 IFR PROFILES WITHIN AIRSPACE CLASS E. WATCH OUT FOR VFR TRAFFIC UNKNWON TO ATC.
- 2 MNM GROUND AND FLIGHT VISIBILITY REQUIRED 1200m.
- 3 CAUTION! EXPECT GLIDER ACTIVITY AT AICHACH.
- 4 BARO-VNAV OPERATIONS NOT AUTHORIZED BELOW -15°C.
- 5 EGNOS CHANNEL 64250 E25A.

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from MAH	IF	MAH	N 48 15 48.35 E 011 18 42.93	-	-	-	-	A4000+	-	-	RNP APCH	-
	TF	MA001	N 48 28 29.42 E 011 09 19.78	-	(T 333.8) 331	14.2	-	A3500+	-	-	RNP APCH	-
Initial APCH from WLD	IF	WLD	N 48 34 45.91 E 011 07 45.79	-	-	-	-	A4000+	-	-	RNP APCH	-
	TF	MA001	N 48 28 29.42 E 011 09 19.78	-	(T 170.6) 168	6.4	-	A3500+	-	-	RNP APCH	-
APCH	TF	BUREG	N 48 27 16.76 E 011 03 51.08	-	(T 251.6) 249	3.8	-	A3500+	-	-	RNP APCH	-
	TF	RW25	N 48 25 37.37 E 010 56 23.75	Y	(T 251.6) 249	5.2	-	-	-	-3.50/50	RNP APCH	-
Missed APCH	CF	MA002	N 48 24 43.87 E 010 52 24.00	Y	(T 251.5) 249	2.8	-	-	185-	-	RNP APCH	-
	CF	MA004	N 48 30 40.32 E 010 49 30.70	-	(T 011.4) 009	-	R	-	185-	-	RNP APCH	-
	TF	MA005	N 48 32 51.31 E 010 59 12.71	-	(T 071.2) 069	6.8	-	@A3500	-	-	RNP APCH	-
	TF	WLD	N 48 34 45.91 E 011 07 45.79	-	(T 071.3) 069	6.0	-	@A4000	-	-	RNP APCH	-

RNAV HOLDING IDENTIFICATION

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	MAH	N 48 15 48.35 E 011 18 42.93	(T 133.9) 131	230-	A4000+	1 min	R	-
HM	WLD	N 48 34 45.91 E 011 07 45.79	(T 134.1) 131	230-	A4000+	1 min	R	-