

TABULAR DESCRIPTION**RNP Z RWY05 CAT A/B/C – Instrument Approach Procedure**

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	VPA°/TCH (m)	Navigation Specification/ Performance
010	IF	GONGA	-	-	-	-	-	+5000	-	-	RNAV1
020	TF	UTUVI	-	045° (048.1°)	-	5.0	-	+3000	-180	-	RNAV1
030	TF	NIBTO	-	045° (048.1°)	-	3.9	-	+3000	-	-	RNP APCH
040	TF	RQ501	Y	045° (048.1°)	-	7.6	-	+940 ⁽¹⁾	-	-	RNP APCH
-	-	RWY05	-	-	-	-	-	@172 ⁽²⁾	-	3.0/15.0	-
050	CF	RQ502	-	168° (171.0°)	3.2 E	-	R	+4000	-160	-	RNP APCH
060	HM	RQ502	Y	348° (351.0°)	3.2 E	-	L	+4000	-185	-	Conventional

(1) For LNAV only

(2) THR Altitude plus TCH

Missed Approach Holding

Path Terminator	Waypoint (FIX)	Inbound Course °M (°T)	Navaid	Outbound leg	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	RQ502 (RDL168/17NM)	348° (351.0°)	PRT VOR/DME	Not exceed 20NM DME	L	+4000	-5000	- 185	3.2 E	Conventional

WAYPOINT LIST

Waypoint Identifier	Coordinates
RQ501	43°47'31.05" N 011°10'37.74" E
RQ502	43°31'48.17" N 011°15'41.08" E