

BIKF RNAV SID RWY 28
Recommended Coding Tables**LUTER 3D**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF235	-	282 (270.0)	+12.4	3.7			-210	RNAV 1 (GNSS)
020	TF	KF236	-	192 (179.7)	+12.4	5.0	L		-240	RNAV 1 (GNSS)
030	TF	KF437	-	106 (093.3)	+12.3	7.5	L	A7000+		RNAV 1 (GNSS)
040	TF	ADOVA	-	080 (068.2)	+12.0	14.6		F120+		RNAV 1 (GNSS)
050	TF	KF438	-	085 (073.5)	+11.9	10.0		F140+		RNAV 1 (GNSS)
060	TF	KF253	-	086 (073.8)	+11.7	11.8		F160+		RNAV 1 (GNSS)
070	TF	LUTER	-	096 (084.5)	+11.2	22.4				RNAV 1 (GNSS)

OSKUM 3D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF235	-	282 (270.0)	+12.4	3.7			-210	RNAV 1 (GNSS)
020	TF	KF236	-	192 (179.7)	+12.4	5.0	L		-240	RNAV 1 (GNSS)
030	TF	KF437	-	106 (093.3)	+12.3	7.5	L	A7000+		RNAV 1 (GNSS)
040	TF	OLGES	-	106 (093.5)	+12.1	9.3		F110+		RNAV 1 (GNSS)
050	TF	KF451	-	106 (093.9)	+11.9	10.0		F130+		RNAV 1 (GNSS)
060	TF	KF439	-	106 (094.2)	+11.8	5.0		F140+		RNAV 1 (GNSS)
070	TF	KF252	-	106 (094.4)	+11.5	14.1		F160+		RNAV 1 (GNSS)
080	TF	OSKUM	-	127 (115.8)	+11.1	18.5				RNAV 1 (GNSS)

PIXUM 2D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF235	-	282 (270.0)	+12.4	3.7			-210	RNAV 1 (GNSS)
020	TF	KF236	-	192 (179.7)	+12.4	5.0	L		-240	RNAV 1 (GNSS)
030	TF	KF437	-	106 (093.3)	+12.3	7.5	L	A7000+		RNAV 1 (GNSS)
040	TF	OLGES	-	106 (093.5)	+12.1	9.3		F110+		RNAV 1 (GNSS)
050	TF	KF239	-	134 (122.2)	+11.8	15.0		F140+		RNAV 1 (GNSS)
060	TF	PIXUM	-	149 (137.0)	+11.2	32.1				RNAV 1 (GNSS)

RIMUM 1D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF235	-	282 (270.0)	+12.4	3.7			-210	RNAV 1 (GNSS)
020	TF	KF236	-	192 (179.7)	+12.4	5.0	L		-240	RNAV 1 (GNSS)
030	TF	KF437	-	106 (093.3)	+12.3	7.5	L	A7000+		RNAV 1 (GNSS)
040	TF	KF467	-	140 (127.4)	+12.1	7.3		F100+		RNAV 1 (GNSS)
050	TF	RIMUM	-	172 (159.8)	+11.3	47.7				RNAV 1 (GNSS)

DELES 3D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF255	-	282 (270.0)	+12.4	3.2				RNAV 1 (GNSS)
020	TF	DELES	-	252 (239.2)	+13.2	56.4				RNAV 1 (GNSS)

RALOV 1D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF255	-	282 (270.0)	+12.4	3.2				RNAV 1 (GNSS)
020	TF	RALOV	-	277 (264.6)	+13.5	55.7				RNAV 1 (GNSS)

SORIR 2D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	CF	KF255	-	282 (270.0)	+12.4	3.2				RNAV 1 (GNSS)
020	TF	KF259	-	315 (303.0)	+13.0	25.9				RNAV 1 (GNSS)
030	TF	SORIR	-	305 (292.1)	+13.6	30.5				RNAV 1 (GNSS)