

TABULAR DESCRIPTION

RNP RWY14 – Instrument Approach Procedure

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/ TCH (m)	Navigation Specification
010	IF	EGFUV	-	-	-	-	-	+5000	-190	-	RNP 1
020	TF	PO502	-	042 (044.7)	-	5.0	-	+3000	-190	-	RNP 1
030	TF	PO501	-	132 (134.8)	-	5.2	R	+3000	-	-	RNP APCH
040	TF	RWY14	Y	132 (134.8)	-	8.2	-	@403 (3)	-	-3.0/ 15.2	RNP APCH
050	CF	ACMIZ	-	132 (134.9)	3.1°E	10.1	-	+4000	-	-	RNP APCH
060	HM	ACMIZ	Y	312 (315.1)	-	-	L	+4000	-200	-	RNAV 1

Holding RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	ACMIZ	312 (315.1)	3.6	1/-	L	+4000	-	-200	3.1°E	RNAV 1
HM	EGFUV	312 (314.8)	3.5	1/-	L	+5000	-	-190	3.1°E	RNAV 1

- (1) RNAV system with holding functionality.
 (2) RNAV system without holding functionality.
 (3) THR Altitude plus TCH.

WAYPOINT LIST

Waypoint Identifier	Coordinates
PO501	45°31'55.26"N - 010°11'00.75"E
PO502	45°35'36.01"N - 010°05'44.37"E

Input data

Operation Type	0
SBAS Provider	1 (EGNOS)
Airport Identifier	LIPO
Runway	14
Runway Letter	0 (None)
Approach Performance Designator	0
Route Indicator	
Reference Path Data Selector	0
Reference Path Identifier	E14A
LTP/FTP Latitude	452610.2315N
LTP/FTP Longitude	0101913.6800E
LTP/FTP Ellipsoidal Height (metres)	150.9
FPAP Latitude	452510.6785N
Delta FPAP Latitude (seconds)	-59.5530
FPAP Longitude	0102038.5120E
Delta FPAP Longitude (seconds)	84.8320
Threshold Crossing Height	50.0
TCH Units Selector	0 (feet)
Glidepath Angle (degrees)	3.00
Course Width (metres)	105.00
Length Offset (metres)	0
HAL (metres)	40.0
VAL (metres)	35.0

Output data

Data Block	10 0F 10 09 0C 0E 00 00 01 34 31 05 6F C4 7F 13 20 D7 6D 04 E5 19 BE 2E FE C0 96 02 F4 01 2C 01 64 00 C8 AF 59 A1 46 FF
Calculated CRC Value	59A146FF