

MUENCHEN
RWY 26R

STANDARD INSTRUMENT DEPARTURE
ROUTES (SID)
RNAV (GPS)

General Remarks	
1.	ATTENTION DEPARTING AIRCRAFT SIMULTANEOUS PARALLEL DEPARTURES IN PROGRESS. PILOTS HAVE TO PROCEED EXACTLY ON EXTENDED CENTERLINE UNTIL STARTING TURNS AS PUBLISHED IN DEPARTURE ROUTES AND SHALL REMAIN ON TWR FREQUENCY UNTIL FURTHER ADVISED.
2.	RWY 26R IS TO BE USED ESPECIALLY FOR DEPARTURES TO N and NE.
3.	1. RNAV-1 or RNP-1 or A-RNP equivalent. 2. GPS required. 3. DME/DME, DME/DME/IRU not authorized.

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
ANKER 9N	ANKER NINE NOVEMBER Climb on course 261° to DM066; RT, to DM064; RT, to DM057; LT, to ANKER (Δ). MAX IAS 220 kt until DM066. MAX IAS 250 kt until DM064.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CA	-	-	-	(T263.7) 261	-	-	A1900+	-	RNAV 1	-
CF	DM066	N 48 21 17.69 E 11 39 39.11	-	(T263.7) 261	-	-	-	220-	RNAV 1	-
TF	DM064	N 48 29 32.67 E 11 37 13.52	-	(T348.9) 346	8.4	-	-	250-	RNAV 1	-
TF	DM057	N 48 32 19.19 E 11 59 09.84	-	(T079.1) 076	14.8	-	-	-	RNAV 1	-
TF	ANKER	N 48 34 21.45 E 12 00 08.38	-	(T017.6) 015	2.1	-	-	-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
EVIVA 5N	EVIVA FIVE NOVEMBER Climb on course 261° to DM066; RT, to DM064; RT, to LASMI (△); LT, to EVIVA (△). MAX IAS 220 kt until DM066. MAX IAS 250 kt until LASMI.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CA	-	-	-	(T263.7) 261	-	-	A1900+	-	RNAV 1	-
CF	DM066	N 48 21 17.69 E 11 39 39.11	-	(T263.7) 261	-	-	-	220-	RNAV 1	-
TF	DM064	N 48 29 32.67 E 11 37 13.52	-	(T348.9) 346	8.4	-	-	-	RNAV 1	-
TF	LASMI	N 48 32 30.00 E 11 43 00.00	-	(T052.4) 049	4.8	-	-	250-	RNAV 1	-
TF	EVIVA	N 48 40 02.75 E 11 42 10.58	-	(T355.9) 353	7.6	-	-	-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
INPUD 2N	INPUD TWO NOVEMBER Climb on course 261° to DM066; RT, via DM064 to DM065; LT, to INPUD (Δ). MAX IAS 220 kt until DM066. MAX IAS 250 kt until DM065.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV-Specification	Remarks
CA	-	-	-	(T263.7) 261	-	-	A1900+	-	RNAV 1	-
CF	DM066	N 48 21 17.69 E 11 39 39.11	-	(T263.7) 261	-	-	-	220-	RNAV 1	-
TF	DM064	N 48 29 32.67 E 11 37 13.52	-	(T348.9) 346	8.4	-	-	-	RNAV 1	-
TF	DM065	N 48 34 12.81 E 11 35 51.01	-	(T348.9) 346	4.8	-	-	250-	RNAV 1	-
TF	INPUD	N 48 40 01.57 E 11 32 29.37	-	(T339.0) 336	6.2	-	-	-	RNAV 1	-