

TABULAR DESCRIPTION

RNP RWY04 – Instrument Approach Procedure via ABLID

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/TCH (m)	Navigation Specification
010	IF	ABLID	-	-	-	-	-	+5000 ⁽³⁾	-210	-	RNAV 1
020	TF	GIVAT	-	042 (045.1)	-	5.0	-	+4000 ⁽³⁾	-200	-	RNAV 1
030	TF	ERMOB	-	042 (045.9)	-	4.0	-	+3000	-	-	RNAV 1
040	TF	PEVIK	-	042 (045.6)	-	3.7	-	+3000	-180	-	RNP APCH
050	TF	RW04	Y	042 (045.6)	-	8.5	-	@277	-	-3.0/17.45	RNP APCH
060	CF	PX701	Y	042 (045.7)	3.3 E	-	-	+1000	-200	-	RNP APCH
070	VI	-	-	199 (202.0)	-	-	R	-	-	-	RNAV 1
080	CF	UNKAV	-	160 (163.1)	3.3 E	-	-	+3000	-200	-	RNAV 1

RNP RWY04 – Instrument Approach Procedure via BOLVO

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/TCH (m)	Navigation Specification
010	IF	BOLVO	-	-	-	-	-	+5000 ⁽³⁾	-210	-	RNAV 1
020	TF	GIVAT	-	313 (315.9)	-	5.0	-	+4000 ⁽³⁾	-200	-	RNAV 1
030	TF	ERMOB	-	042 (045.9)	-	4.0	R	+3000	-	-	RNAV 1
040	TF	PEVIK	-	042 (045.6)	-	3.7	-	+3000	-180	-	RNP APCH
050	TF	RW04	Y	042 (045.6)	-	8.5	-	@277	-	-3.0/17.45	RNP APCH
060	CF	PX701	Y	042 (045.7)	3.3 E	-	-	+1000	-200	-	RNP APCH
070	VI	-	-	199 (202.0)	-	-	R	-	-	-	RNAV 1
080	CF	UNKAV	-	160 (163.1)	3.3 E	-	-	+3000	-200	-	RNAV 1

RNP RWY04 – Instrument Approach Procedure via RIVEV

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation (°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA (°)/TCH (m)	Navigation Specification
010	IF	RIVEV	-	-	-	-	-	+5000 ⁽³⁾	-210	-	RNAV 1
020	TF	GIVAT	-	133 (135.7)	-	5.0	-	+4000 ⁽³⁾	-200	-	RNAV 1
030	TF	ERMOB	-	042 (045.9)	-	4.0	L	+3000	-	-	RNAV 1
040	TF	PEVIK	-	042 (045.6)	-	3.7	-	+3000	-180	-	RNP APCH
050	TF	RW04	Y	042 (045.6)	-	8.5	-	@277	-	-3.0/17.45	RNP APCH
060	CF	PX701	Y	042 (045.7)	3.3 E	-	-	+1000	-200	-	RNP APCH
070	VI	-	-	199 (202.0)	-	-	R	-	-	-	RNAV 1
080	CF	UNKAV	-	160 (163.1)	3.3 E	-	-	+3000	-200	-	RNAV 1

Missed Approach Holding procedure RNAV

Path Terminator	Waypoint identifier	Inbound Course °M(°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	UNKAV	160 (163.1)	3.0	- / 3.9	R	+3000	-	-185	3.3 E	RNAV 1

REMARKS

- (1) RNAV system with holding functionality
(2) RNAV system without holding functionality
(3) 3000 FT ATC Discretion

Waypoints Table formatted according ARINC 424 standards

Waypoint	Latitude	Longitude
PX701	N45253229	E010555556

SBAS FAS DATA BLOCK LIPX RNP RWY04

Input Data	
Parameters	Values
Operation Type	0
SBAS Provider	1 (EGNOS)
Airport Identifier	LIPX
Runway	04
Runway Letter	0 (None)
Approach Performance Designator	0
Route Indicator	
Reference Path Data Selector	0
Reference Path Identifier	E04A
LTP/FTP Latitude	452315.6585N
LTP/FTP Longitude	0105236.7185E
LTP/FTP Ellipsoidal Height (metres)	111.4
FPAP Latitude	452423.7485N
Delta FPAP Latitude (seconds)	68.0900
FPAP Longitude	0105415.7515E
Delta FPAP Longitude (seconds)	99.0330
Threshold Crossing Height	17.45
TCH Units Selector	1 (meters)
Glidepath Angle (degrees)	3.00
Course Width (metres)	105.00
Length Offset (metres)	0
HAL (metres)	40.0
VAL (metres)	35.0

Output Data	
Data Block	10 18 10 09 0C 04 00 00 01 34 30 05 95 70 7A 13 DD F7 AA 04 5A 18 F4 13 02 B2 05 03 5D 81 2C 01 64 00 C8 AF BA 4E AC 4A
Calculated CRC Value	BA4EAC4A