

WAAS CH 77500 W18A	APP CRS 183°	Rwy Idg TDZE 748 Apt Elev 748
--	------------------------	---

RNAV (GPS) Y RWY 18L

CHARLOTTE/DOUGLAS INTL (CLT)

RNP APCH

⚠

Circling NA at night. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

⚠

Rwy 18L helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C.

MISSED APPROACH: Climb to 1300 then climbing left turn to 4000 direct LOCAS and hold.

D-ATIS	CHARLOTTE APP CON	CHARLOTTE TOWER	GND CON	CLNC DEL
ARR 121.15	(001°-119°) 128.32	(Rwys 18L-36R) 118.1 257.8	121.8 348.6 (WEST)	127.15
DEP 132.1	(120°-295°) 120.05	(Rwy 18C-36C) 126.4 257.8	121.9 348.6 (EAST)	348.6
	(296°-360°) 134.75	(Rwy 18R-36L) 133.35 257.8		
	(180°-359°) 257.2			
	(360°-179°) 307.8			

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 76).				
CAVVI SNACK GILGE QUWED EGUUL ZIMOG RW18L				
6000 5000 4000 3000 2400 2400 1620				
GP 3.00° TCH 56				
-3.2 NM -3.2 NM 3.2 NM 1.9 NM 2.4 NM 1.5 NM 1.1 NM				
CATEGORY	A	B	C	D
LPV DA	1002/40		254 (300-¾)	
LNAV/VNAV DA	1216-1⅜		468 (500-1⅝)	
LNAV MDA	1180/55		1180-1¼ 432 (500-1¼)	
CIRCLING	1380-1 632 (700-1)		1500-2¼ 752 (800-2¼) 1500-2½ 752 (800-2½)	

CHARLOTTE, NORTH CAROLINA

Amtd 5 15AUG19

35°13'N-80°57'W

CHARLOTTE/DOUGLAS INTL (CLT)

RNAV (GPS) Y RWY 18L