

ILS or LOC Y RWY 12

LOC I-MJW

109.9

APCH CRS

118°

Rwy Idg

13,198

TDZE

1666

Arprt Elev

1666

[USAF]

MINOT AFB

(KMIB)

RADAR or DME required.

* When ALS inop, increase RVR to 40 and vis to ¾ mile.

** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.

*** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1½ miles.

**** Circling not authorized N of Rwy 12-30.

ALSIF-1

MISSED APPROACH: Climb to 5000 via MIB TACAN R-112 direct AMIRE and hold.

ATIS

278.8

MINOT APP CON

119.6 363.8

MINOT TOWER

120.65 253.5

GND CON

134.0 275.8

CLNC DEL

326.2

LOCALIZER 109.9

I-MJW

EMERG SAFE ALT 100 NM 4700

KESNE MIB 15

5000

118°

3200

2520

2.5 NM

2.5 NM

0.6 NM

GS 2.50°

TCH 48

5000

MIB R-112

AMIRE MIB 15

ELEV 1666

TDZE 1666

118°

A1

P

TWR

13,198 ± 300

30

A1

CATEGORY	A	B	C	D	E
S-ILS 12 *	1866/24		200	(200-½)	
S-LOC 12 **	2080/24 414 (500-½)		2080/40 414		(500-¾)
CIRCLING ****	2120-1 454 (500-1)	2140-1 474 (500-1)	2180-1½ 514 (600-1½)	2320-2 654 (700-2)	2320-2¼ 654 (700-2¼)
LOCAL ALTIMETER WITHOUT LAST STEPDOWN FIX					
S-LOC 12 ***	2200/24 534 (600-½)		2200/55 534		(600-1)
CIRCLING ****	2200-1 534 (600-1)		2200-1½ 534 (600-1½)		2320-2 654 (700-2) 2320-2¼ 654 (700-2¼)

HIRL Rwy 12-30

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

MINOT, NORTH DAKOTA

48°25'N-101°21'W

MINOT AFB (KMIB)

Amdd 2 16MAY24

ILS or LOC Y RWY 12

NC-1, 20 MAR 2025 to 17 APR 2025

NC-1, 20 MAR 2025 to 17 APR 2025