

TABULAR DESCRIPTION RNP Z RWY 10- VIPT(CAT A/B):-

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Distance/ Time	Turn Direction	Altitude (ft)	Speed Limit (Kt)	VPA/TCH °/ft	Navigation Specification
					NM/Min					
10	IF	PT403					+4000.00			RNP APCH
20	TF	PT003		7.64(8.39)	4.00		+2600.00			RNP APCH
10	IF	HW					+4000.00			RNP APCH
20	TF	PT405		322.73(323.48)	5.85		+4000.00			RNP APCH
30	TF	PT401		277.69 (278.44)	4.18		+4000.00			RNP APCH
40	TF	PT003		187.66 (188.41)	4.00		+2600.00			RNP APCH
10	IF	PT401					+4000.00			RNP APCH
20	TF	PT003		187.66 (188.41)	4.00		+2600.00			RNP APCH
10	IF	PT003					+2600.00			RNP APCH
20	TF	PT007		97.69 (98.44)	4.14		@2000.00			RNP APCH
30	TF	RW10	Y	97.66 (98.41)	3.71		@818.55		-3.00/50.0	RNP APCH
40	CF	PT406	Y	97.67 (98.42)						RNP APCH
50	DF	HW				L	+4000.00			RNP APCH
10	HM	HW	Y	322.73 (323.48)	1MIN	R	+4000.00	-180		RNP APCH

WAYPOINT LIST RNP Z RWY 10 VIPT (CAT A/B) :-

Waypoint Identifier	Coordinates
HW	N 29:01:51.56E 79:28:25.95
PT403	N 28:59:15.16E 79:18:24.05
PT003	N 29:03:13.19E 79:19:04.03
PT405	N 29:06:34.37E 79:24:27.39
PT401	N 29:07:11.22E 79:19:44.06
PT406	N 29:00:53.71E 79:36:51.85
PT007	N 29:02:36.53E 79:23:44.47
RW10	N 29:02:03.82E 79:27:55.69