

Remarks	
6	
06	Nil
24	Nil

EDNY AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
06	LIL_LIH Sequence flash available	G LIH	3.1° 49.00 ft	-	Up to 1186 m: W LIH; 1186 – 1786 m: R/W LIH; 1786 – 2086 m: R LIH. 15 m spacing	W LIH	R LIH	-
24	LIL_LIH Sequence flash available	G LIH	3.0° 55.00 ft	W LIH	Up to 1250 m: W LIH; 1250 – 1850 m: R/W LIH; 1850 – 2150 m: R LIH. 15 m spacing	W LIH	R LIH	-

Remarks	
10	
06	Nil
24	Nil

EDNY AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDNY 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL TWY Center line lights of TWYs A, B, E, F, N: G LIH Y/G colour-coded between RWY and CAT II/III taxi-holding positions within the 'sensitive area'.
4	Secondary power supply including switch-over time	Available CAT I: 1 SEC CAT II/III: 1 SEC
5	Remarks	Nil