

TABULAR DESCRIPTION

RNP Z RWY 32 – Instrument Approach Procedure via ADSAS

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH (m)	Navigation Specification (4)
010	IF	ADSAS	-	-	-	-	-	+5000 (1)	-210	-	RNAV 1/RNP 1
020	TF	NIPLI	-	042 (045.2)	-	6.9	-	+4000 (1)	-200	-	RNAV 1/RNP 1
030	TF	PO551	-	312 (315.1)	-	4.0	L	+3000	-	-	RNP APCH
040	TF	PO550	Y	312 (315.0)	-	7.4	-	+720 (2)	-	-	RNP APCH
-	-	RWY32	-	-	-	-	-	@389 (3)	-	-3.0/17	RNP APCH
050	DF	PO553	-	-	-	-	R	-	-190	-	RNP APCH
060	TF	UPGAV	-	133 (135.9)	-	9.3	-	+5000 (5)	-190	-	RNP APCH
070	HM	UPGAV	Y	133 (136.0)	-	-	L	+5000 (6)	-210	-	RNAV 1

RNP Z RWY 32 – Instrument Approach Procedure via ELDIP

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH (m)	Navigation Specification (4)
010	IF	ELDIP	-	-	-	-	-	+5000 (1)	-210	-	RNAV 1/RNP 1
020	TF	NIPLI	-	312 (315.1)	-	5.0	-	+4000 (1)	-200	-	RNAV 1/RNP 1
030	TF	PO551	-	312 (315.1)	-	4.0	-	+3000	-	-	RNP APCH
040	TF	PO550	Y	312 (315.0)	-	7.4	-	+720 (2)	-	-	RNP APCH
-	-	RWY32	-	-	-	-	-	@389 (3)	-	-3.0/17	RNP APCH
050	DF	PO553	-	-	-	-	R	-	-190	-	RNP APCH
060	TF	UPGAV	-	133 (135.9)	-	9.3	-	+5000 (5)	-190	-	RNP APCH
070	HM	UPGAV	Y	133 (136.0)	-	-	L	+5000 (6)	-210	-	RNAV 1

RNP Z RWY 32 – Instrument Approach Procedure via UPGAV

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH (m)	Navigation Specification (4)
010	IF	UPGAV	-	-	-	-	-	+5000 (1)	-210	-	RNAV 1/RNP 1
020	TF	NIPLI	-	223 (226.1)	-	6.6	-	+4000 (1)	-200	-	RNAV 1/RNP 1
030	TF	PO551	-	312 (315.1)	-	4.0	R	+3000	-	-	RNP APCH
040	TF	PO550	Y	312 (315.0)	-	7.4	-	+720 (2)	-	-	RNP APCH
-	-	RWY32	-	-	-	-	-	@389 (3)	-	-3.0/17	RNP APCH
050	DF	PO553	-	-	-	-	R	-	-190	-	RNP APCH
060	TF	UPGAV	-	133 (135.9)	-	9.3	-	+5000 (5)	-190	-	RNP APCH
070	HM	UPGAV	Y	133 (136.0)	-	-	L	+5000 (6)	-210	-	RNAV 1

(1) MEA 3000ft ATC discretion

(2) OCA

(3) THR Altitude plus TCH

(4) For “monitoring and alerting” reasons, RNP 1 specification is required in case of radar service unavailability or degradation

(5) MCA 4000ft ATC discretion

(6) MHA 4000ft ATC discretion

Holding RNAV

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	UPGAV	133 (136.0)	4.0	-/5.1	L	+5000 (3)	-	-210	3.1°E	RNAV 1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) MHA 4000ft ATC discretion

WAYPOINT LIST

Waypoint Identifier	Coordinates
PO550	45°24'39.17"N - 010°21'23.31"E
PO551	45°19'25.32"N - 010°28'48.75"E
PO553	45°27'51.55"N - 010°30'23.93"E