

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**

**JEDDAH/King Abdulaziz Intl (OEJN)
RNAV RWY 34L**

VEMEM 1A MISAM 1A MUVOL 1A NOMDA 1A BOSUT 2L EGMEG 2L
IMDAP 2L ULULU 2L VEMEM 2L MISAM 2L MUVOL 2L NOMDA 2L

TABULAR DESCRIPTION

RNAV RWY 34L											
Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course M°(T°)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/TCH (°/ft)	Navigation Specification
BOSUT 2L ARRIVAL											
010	IF	BOSUT	-	-	-	-	-	-	-	-	RNAV 1
020	TF	JN840	-	307(310.8)	-3.8	9.8	-	-13000	-	-	RNAV 1
030	TF	TAPSU	-	307(310.7)	-3.8	5.3	-	-	-	-	RNAV 1
040	TF	REXED	-	331(335.2)	-3.8	9.1	-	-8500	@210	-	RNAV 1
050	TF	ITUXI	-	006(010.2)	-3.8	11.3	-	+5000	-	-	RNAV 1
060	TF	JN812	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	VEDIR	-	336(339.7)	-3.8	6.0	-	@3100	-	-	RNAV 1
EGMEG 2L ARRIVAL											
010	IF	EGMEG	-	-	-	-	-	-	-	-	RNAV 1
020	TF	TADMA	-	070(073.7)	-3.8	15.0	-	-	-	-	RNAV 1
030	TF	JN830	-	070(073.8)	-3.8	8.3	-	-11000	-	-	RNAV 1
040	TF	REXED	-	063(066.0)	-3.8	18.5	-	-8500	@210	-	RNAV 1
050	TF	ITUXI	-	006(010.2)	-3.8	11.3	-	+5000	-	-	RNAV 1
060	TF	JN812	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	VEDIR	-	336(339.7)	-3.8	6.0	-	@3100	-	-	RNAV 1
IMDAP 2L ARRIVAL											
010	IF	IMDAP	-	-	-	-	-	-	-	-	RNAV 1
020	TF	OBTUG	-	241(244.5)	-3.8	17.3	-	+13000	@210	-	RNAV 1
030	TF	TOTNU	-	225(229.0)	-3.8	14.0	-	-	-	-	RNAV 1
040	TF	JN818	-	156(159.8)	-3.8	9.2	-	-	-	-	RNAV 1
050	TF	GEVUS	-	156(159.7)	-3.8	6.0	-	+10000	-	-	RNAV 1
060	TF	JN908	-	156(159.7)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	JN906	-	156(159.7)	-3.8	6.0	L	-	-	-	RNAV 1
080	TF	ITUXI	-	066(069.7)	-3.8	6.0	L	+5000	-	-	RNAV 1
090	TF	JN812	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
100	TF	VEDIR	-	336(339.7)	-3.8	6.0	-	@3100	-	-	RNAV 1
ULULU 2L ARRIVAL											
010	IF	ULULU	-	-	-	-	-	-	-	-	RNAV 1
020	TF	GEVUS	-	087(090.5)	-3.8	10.5	-	+10000	@210	-	RNAV 1
030	TF	JN908	-	156(159.7)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN906	-	156(159.7)	-3.8	6.0	L	-	-	-	RNAV 1
050	TF	ITUXI	-	066(069.7)	-3.8	6.0	L	+5000	-	-	RNAV 1
060	TF	JN812	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
070	TF	VEDIR	-	336(339.7)	-3.8	6.0	-	@3100	-	-	RNAV 1
VEMEM 2L ARRIVAL (Use on ATC instruction only)											
010	IF	VEMEM	-	-	-	-	-	-	-	-	RNAV 1
020	TF	RABTU	-	233(236.8)	-3.8	10.0	L	+FL170	@250	-	RNAV 1
030	TF	JN799	-	150(153.6)	-3.8	6.0	-	-	-	-	RNAV 1
040	TF	JN797	-	164(167.4)	-3.8	6.0	-	-	-	-	RNAV 1
050	TF	RABEP	-	177(181.2)	-3.8	6.1	R	+FL170	@250	-	RNAV 1
060	TF	IMDAP	-	274(278.2)	-3.8	25.0	-	+FL150	-	-	RNAV 1
070	TF	OBTUG	-	241(244.5)	-3.8	17.3	-	+13000	@210	-	RNAV 1
080	TF	TOTNU	-	225(229.0)	-3.8	14.0	-	-	-	-	RNAV 1
090	TF	JN818	-	156(159.8)	-3.8	9.2	-	-	-	-	RNAV 1
100	TF	GEVUS	-	156(159.7)	-3.8	6.0	-	+10000	-	-	RNAV 1
110	TF	JN908	-	156(159.7)	-3.8	6.0	-	-	-	-	RNAV 1
120	TF	JN906	-	156(159.7)	-3.8	6.0	L	-	-	-	RNAV 1
130	TF	ITUXI	-	066(069.7)	-3.8	6.0	L	+5000	-	-	RNAV 1
140	TF	JN812	-	336(339.7)	-3.8	6.0	-	-	-	-	RNAV 1
150	TF	VEDIR	-	336(339.7)	-3.8	6.0	-	@3100	-	-	RNAV 1

CHANGE: Table updated.

AMDT: Original, 10 AUG 23

ICAO PANS OPS