EDDL AD 2.9 Surface movement guidance and control system and markings

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system at aircraft stands	NIL
2	RWY and TWY markings and LGT	RWY designations, THRs, RWY centre lines, touchdown zones TWY centre lines, TWY taxi-holding positions Apron 1, 2, 3: taxiing guide lines to the parking positions TWY and destination indicators are reflecting and/or lighted from the inside.
3	Stop bars	R LIH
4	Remarks	See EDDL AD 2-20

EDDL AD 2.10 Aerodrome obstacles

Refer to AD 2 EDDL 2-11 AERODROME OBSTACLE CHART - ICAO TYPE A RWY 05R/23L
Refer to AD 2 EDDL 2-13 AERODROME OBSTACLE CHART - ICAO TYPE A RWY 05L/23R

EDDL AD 2.11 Meteorological information provided

1	Associated MET Office	Meteorological Advisory Center (MAC) Essen
2	Hours of service MET Office outside hours	H24
3	Office responsible for TAF preparation Periods of validity	MAC Essen 30 HR
4	Trend forecast Interval of issuance	TREND 30 MIN
5	Briefing/consultation provided	see No. 10 by phone
6	Flight documentation Language(s) used	Charts, abbreviated plain language text 2) English, German
7	Charts and other information available for briefing or consultation	SWC, W/T charts, SIGMET, METAR/TAF en-route 2)
8	Supplementary equipment available for providing information	NIL
9	ATS units provided with information	Düsseldorf TWR
10	Additional information (limitation of service, etc.)	Individual weather consultation: Tel.: 0900 50 77 22 3 1) 1) Value-added service prices see GEN 3.5 2) Provided by: www.flugwetter.de

EDDL AD 2.12 Runway physical characteristics

Designations RWY NR	TRUE BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
05L	52.80°	2700 x 45	100/R/B/W/T CONC	N 51 17 07.132 E 006 45 07.643	THR 115.7 ft
23R	232.80°	2700 x 45	100/R/B/W/T CONC	N 51 17 48.248 E 006 46 33.931	THR 123.2 ft
05R	52.80°	3000 x 45	100/R/B/W/T CONC	N 51 16 52.445 E 006 45 19.467	THR 119.9 ft
23L	232.80°	3000 x 45	100/R/B/W/T CONC	N 51 17 39.431 E 006 46 58.073	THR 137.7 ft

© DFS Deutsche Flugsicherung GmbH