LOC/DME I-BNA 109.9 Chan 36	APP CRS 021°	Rwy ldg 7702 TDZE 599 Apt Elev 599

ILS or LOC RWY 2L

NASHVILLE INTL (BNA)

Simultaneous approach authorized with Rwy 2R. DME or radar required.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 on heading 240° and on BNA VORTAC R-270 to BEVEE/BNA VORTAC 22.4 DME and hold.

D-ATIS	NASHVILLE APP CON	NASHVILLE TOWER	GND CON	CLNC DEL	CPDLC
135.1	118.4 360.7	118.6 257.8	121.9 348.6	126.05	

DME or RADAR REQUIRED

CATEGORY	A	B	C	D
S-ILS 2L	799/18 200 (200-½)			
S-LOC 2L	980/24 381 (400-½)		980/35 381 (400-⅝)	
C CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)

FAF to MAP 5.8 NM

Knots	60	90	120	150	180
Min:Sec	5:48	3:52	2:54	2:19	1:56

SE-1, 20 MAR 2025 to 17 APR 2025