

STAR RNP 0.3 for Helicopters
Description Tables

WARNING

- (1) Procedures partially outside controlled airspace interfering with Trento, Bolzano, Cles and Fiemme and Arco Procedures
(2) Procedure for CAT H only

PEWOC 1E

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	PEWOC	-	-	-	-	-	+9000	-	RNP 0.3
TF	KA408	-	203 (206.4)	-	9.8	-	+9000	100	RNP 0.3
TF	KA407	-	269 (272.6)	-	5.2	-	+7800	-	RNP 0.3
TF	KA406	-	243 (246.4)	-	4.4	-	+7400	-	RNP 0.3
TF	UVIBE	-	258 (261.4)	-	6.3	-	+7400	-	RNP 0.3

PEWOC 1F

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	PEWOC	-	-	-	-	-	+9000	-	RNP 0.3
TF	KA408	-	203 (206.3)	-	9.8	-	+9000	100	RNP 0.3
TF	KA407	-	269 (272.6)	-	5.2	-	+7800	-	RNP 0.3
TF	KA406	-	243 (246.4)	-	4.4	-	+6200	-	RNP 0.3
TF	AVCOL	-	225 (228.8)	-	7.6	-	+6200	-	RNP 0.3

Holding RNP 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	UVIBE	213 (216)	1.8	1/1.9	L	9000	-	90	3 E	RNP1
HM	AVCOL	064 (067)	1.9	1 / 2.1	R	9000	-	100	3 E	RNP1

REMARK

- (1) RNAV system with holding functionality
(2) RNAV system without holding functionality

WAYPOINT LIST

Waypoint Identifier	Coordinates
AVCOL	46°10'31.0" N 011°13'20.8" E
KA406	46°15'31.8" N 011°21'34.6" E
KA407	46°17'16.9" N 011°27'21.9" E
KA408	46°17'02.7" N 011°34'51.3" E
PEWOC	46°25'50.5" N 011°41'08.6" E
UVIBE	46°14'35.3" N 011°12'39.6" E