

RJSS / SENDAI

RNAV SID and TRANSITION

CHANGE : Navigation Specification(Basic RNP1 $\rightarrow$ RNP1).

STANDARD DEPARTURE CHART - INSTRUMENT

RJSS / SENDAI

RNAV SID and TRANSITION

STEED FOUR DEPARTURE

RWY09

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	091 (082.5)	-8.3	-	-	+500	-	-	RNP1
002	DF	SS901	Y	-	-8.3	-	-	-	-	-	RNP1
003	DF	MUSBI	-	-	-8.3	-	R	+5000	-	-	RNP1
004	TF	STEED	-	189 (180.9)	-8.3	12.8	-	-	-	-	RNP1

RWY27

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	271 (262.5)	-8.3	-	-	+500	-	-	RNP1
002	DF	BUBLE	-	-	-8.3	-	L	-	-	-	RNP1
003	TF	MUSBI	-	189 (180.9)	-8.3	7.2	-	+5000	-	-	RNP1
004	TF	STEED	-	189 (180.9)	-8.3	12.8	-	-	-	-	RNP1

RIKYU TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	STEED	-	-	-8.3	-	-	-	-	-	RNP1
002	TF	RIKYU	-	257 (248.4)	-8.3	27.3	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).