

BARI / Palese
SID RNAV 1 or RNP1 RWY 07

REMARKS

- 1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation;
- 2) Minimum Climb Gradient: 7.2% (440 FT/NM) for FASAN 5W and TOPNO 5Y only;
- 3) Minimum Climb Gradient: 6.0% (365 FT/NM) for all other SID.

BANAV 6W

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	UVOKA	-	341 (344.6)	-	4.3	-	+5000	-	RNAV1/RNP1 (1)
TF	PERAV	-	016 (019.8)	-	9.5	-	+ FL 100	-	RNAV1/RNP1 (1)
TF	BANAV	-	012 (015.9)	-	12.5	-	+ FL 100	-	RNAV1/RNP1 (1)

DIVKU 5W

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	UVOKA	-	341 (344.6)	-	4.3	-	+5000	-	RNAV1/RNP1 (1)
TF	BD606	-	251 (254.5)	-	15.9	L	+ FL 110	-	RNAV1/RNP1 (1)
TF	BD607	-	251 (254.5)	-	14.0	-	-	-	RNAV1/RNP1 (1)
TF	DIVKU	-	307 (311.1)	-	23.3	-	-	-	RNAV1/RNP1 (1)

EKMUR 5W (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	UVOKA	-	341 (344.6)	-	4.3	-	+5000	-	RNAV1/RNP1 (1)
TF	EKMUR	-	274 (277.8)	-	15.5	-	+ FL 90	-	RNAV1/RNP1 (1)

FASAN 5W (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD651	-	087 (091.0)	-	3.7	-	-	-	RNAV1/RNP1 (1)
TF	BD652	-	132 (135.8)	-	6.6	-	+FL 80	-	RNAV1/RNP1 (1)
TF	FASAN	-	132 (135.8)	-	20.4	-	+ FL 100	-	RNAV1/RNP1 (1)

PERAV 5W (ATC discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	UVOKA	-	341 (344.6)	-	4.3	-	+5000	-	RNAV1/RNP1 (1)
TF	PERAV	-	016 (019.8)	-	9.5	-	+FL 100	-	RNAV1/RNP1 (1)

PISIP 6W

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	UVOKA	-	341 (344.6)	-	4.3	-	+5000	-	RNAV1/RNP1 (1)
TF	PISIP	-	307 (311.4)	-	13.7	-	+FL 120	-	RNAV1/RNP1 (1)

TOPNO 5W

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD602	-	341 (344.6)	-	7.7	-	+4500	-	RNAV1/RNP1 (1)
TF	BD603	-	251 (254.6)	-	17.1	-	+FL 95	-	RNAV1/RNP1 (1)
TF	TOPNO	-	224 (228.3)	-	25.4	-	+ FL 110	-	RNAV1/RNP1 (1)

TOPNO 5Y

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD651	-	087 (091.0)	-	3.7	-	-	-	RNAV1/RNP1 (1)
TF	BD652	-	132 (135.8)	-	6.6	R	+FL 80	-	RNAV1/RNP1 (1)
TF	BD653	-	222 (225.8)	-	6.6	-	+FL 90	-240	RNAV1/RNP1 (1)
TF	TOPNO	-	260 (263.7)	-	41.3	-	+ FL 110	-	RNAV1/RNP1 (1)

VURKE 5W

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	066 (069.5)	4 E	-	-	+508	-	RNAV1/RNP1 (1)
CF	BD601	-	066 (069.5)	4 E	-	-	+2500	-240	RNAV1/RNP1 (1)
TF	BD651	-	087 (091.1)	-	3.7	-	-	-	RNAV1/RNP1 (1)
TF	PIKEL	-	087 (091.1)	-	6.5	-	+4500	-	RNAV1/RNP1 (1)
TF	VURKE	-	078 (082.2)	-	42.9	-	+FL 100	-	RNAV1/RNP1 (1)

WAYPOINT LIST

Waypoint Identifier	Coordinates
BD601	41° 11' 14.69"N 016° 56' 02.29" E
BD602	41° 18' 38.56"N 016° 53' 20.06" E
BD603	41° 14' 04.02"N 016° 31' 32.74" E
BD606	41° 18' 31.41"N 016° 31' 31.14" E
BD607	41° 14' 43.42"N 016° 13' 41.17" E
BD651	41° 11' 10.74"N 017° 00' 52.96" E
BD652	41° 06' 28.77"N 017° 06' 55.50" E
BD653	41° 01' 52.07"N 017° 00' 39.36" E