INSTRUMENT APPROACH CHART

RJBB / KANSAI INTL — ILS Z or LOC Z RWY06R (CAT Ⅱ)

KANSAI APP	ILS - LOC	KANSAI TOWER	RADAR AVBL
120.25 - 125.5 258.3	108.1 IKD ILS-GP 334.7 ILS-DME CH-18X	118.2 - 118.05 126.2 - 236.8	ATIS 127.85

NM to IKD	FAF	4	3	2	MAPt
ALT(3.0˚ APCH Path)	1300	1273	954	635	–

MISSED APPROACH

Direct to AMBER, to B6R62, to B6R63 to MAIKO, to SASVO and hold at 4000FT. Contact KANSAI APP.

Timing not authorized for defining the MAPt.

Missed APCH climb gradient MNM 5 .0%

MINIMA THR elev. 5 AD elev. 17

CAT	CAT Ⅱ			CAT Ⅰ		LOC		CIRCLING	
	DA(H)	RA	RVR	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	105 (100)	100	300	205 (200)	550	390 (385)	900	610 (593)	1600
B							1000		
C									2400
D/DL							1400		3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to NORTH side of RWY only.

CHANGE : ATVID, MIBIB, OTBON, B6R62, B6R63, SASVO, NOLOP established. ALVIS abolished. PROC course. MSA. ALT(3.0° APCH Path). Missed APCH course. OCA(H). DME to IKD. Missed APCH climb gradient MNM added. NM to THR. Note added.