

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
26 TWY B	2300 1500	2300 1500	2300 1500	2300 NIL

Remarks	
6	
08	Nil
26	Nil

EDVE AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
08	ALSAF LIH 720 m Sequence flash available	G LIH	3.0° 49.00 ft	-	-	Up to 300 m: R LIH; 300 – 1700 m: W LIH 1700 – 2300 m: Y LIH. 60 m spacing.	R LIH	-
26	ALSAF LIH 900 m Sequence flash available	G LIH	3.0° 53.00 ft	-	-	Up to 1700 m: W LIH; 1700 – 2300 m: Y LIH. 60 m spacing.	R LIH	-

Remarks	
10	
08	Nil
26	Nil

EDVE AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDVE 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs A, B, C (E OF APRON), C (W OF APRON), D, E, F, G, H, K: B LIL
4	Secondary power supply including switch-over time	Available / <1 SEC
5	Remarks	Nil