

CHANIA/ IOANNIS DASKALOGIANNIS AIRPORT

SIDs RWY 29R

SUD VOR/DME

GENERAL

1. When for these SIDs an altitude higher than the transition altitude is designated, then ATC unit shall specify an equivalent flight level.

DESIGNATOR	DESCRIPTION	MAX IAS /BANK ANGLE	MINIMUM CLIMB GRADIENT (PDG).	ALTITUDES
PLH 1L	Climb straight ahead. At 3200ft turn right to SUD. After SUD turn right to track 274°, intercept and follow R 229 SUD to PLH.	210KT/15° until the turn at 3200ft is completed . 230KT/25° until the turn at SUD is completed .	6.0% (365 ft/NM) up to 11000 ft for ATC purposes.	Cross SUD at 8000ft or above. Cross R 229 SUD/ 7 DME FIX at 11000ft or above.
BAVES 1L	Climb straight ahead. At 3200ft turn right to SUD. After SUD turn left, intercept and follow R 097 SUD and join AWY J65 to BAVES.	210KT/15° until the turn at 3200ft is completed .	6.0% (365 ft/NM) up to 9000 ft for ATC purposes.	Cross SUD at 8000ft or above. Cross R 097 SUD/ 28 DME FIX at 9000ft or above.
OTREX 1L	Climb straight ahead. At 3200ft turn right to SUD. After SUD turn left, intercept and follow R 136 SUD. At R 136 SUD / 25 DME FIX turn left and join AWY R78/M978 to OTREX.	210KT/15° until the turn at 3200ft is completed . 230KT/25° until the turn at R 136 SUD / 25 DME FIX is completed .	6.0% (365 ft/NM) up to 11000 ft for ATC purposes.	Cross SUD at 8000ft or above. Cross R 136 SUD/ 7 DME FIX at 11000ft or above.