

ALGHERO/Fertilia
STAR RNAV1 RWY 20

CORSI 2Z (Available only for traffic departing from LFKJ)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	CORSI	-	-	-	-	-	-	-	RNAV1
TF	EA404	-	207 (209.6)	-	14.4	-	+FL90	-	RNAV1
TF	EA405	-	207 (209.6)	-	6.4	-	+6000	-	RNAV1
TF	UPOXE	-	211 (213.7)	-	13.8	-	+3000	-210	RNAV1

ELSAG 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ELSAG	-	-	-	-	-	-	-	RNAV1
TF	EA409	-	080 (082.3)	-	6.0	-	+FL90	-	RNAV1
TF	MASSU	-	024 (026.0)	-	17.0	-	+4000	-	RNAV1
TF	UPOXE	-	112 (114.7)	-	6.0	-	+3000	-210	RNAV1

MINKA 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	MINKA	-	-	-	-	-	-	-	RNAV1
TF	EA406	-	245 (247.2)	-	6.6	-	+6000	-	RNAV1
TF	SOKVO	-	276 (278.9)	-	8.6	-	+4000	-	RNAV1
TF	UPOXE	-	292 (294.7)	-	6.0	-	+3000	-210	RNAV1

MOROB 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	MOROB	-	-	-	-	-	-	-	RNAV1
TF	SOKVO	-	311 (313.2)	-	11.7	-	+4000	-	RNAV1
TF	UPOXE	-	292 (294.7)	-	6.0	-	+3000	-210	RNAV1

PELOS 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	PELOS	-	-	-	-	-	-	-	RNAV1
TF	EA400	-	167 (169.3)	-	5.6	-	+FL90	-	RNAV1
TF	EA401	-	167 (169.3)	-	6.1	-	+6000	-	RNAV1
TF	MASSU	-	140 (142.6)	-	6.5	-	+4000	-	RNAV1
TF	UPOXE	-	112 (114.7)	-	6.0	-	+3000	-210	RNAV1

REVDO 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	REVDO	-	-	-	-	-	-	-	RNAV1
TF	EA402	-	201 (203.6)	-	11.9	-	+FL90	-	RNAV1
TF	EA403	-	201 (203.5)	-	6.3	-	+6000	-	RNAV1
TF	UPOXE	-	199 (201.8)	-	13.8	-	+3000	-210	RNAV1

SODIO 2Z

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SODIO	-	-	-	-	-	-	-	RNAV1
TF	EA407	-	330 (332.1)	-	11.6	-	+FL100	-	RNAV1
TF	EA408	-	330 (332.0)	-	5.2	-	+FL90	-	RNAV1
TF	SOKVO	-	022 (024.8)	-	18.1	-	+4000	-	RNAV1
TF	UPOXE	-	292 (294.7)	-	6.0	L	+3000	-210	RNAV1

HOLDING RNAV1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min./Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	UPOXE	202 (204.7)	4.0	-/4.9	R	+3000	-	-210	3.0	RNAV1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

WAYPOINT LIST

Waypoint Identifier	Coordinates
EA400	41°04'11.2" N 008°11'04.2" E
EA401	40°58'09.3" N 008°12'34.6" E
EA402	41°09'03.4" N 008°35'06.9" E
EA403	41°03'14.3" N 008°31'45.7" E
EA404	41°07'28.0" N 008°39'16.5" E
EA405	41°01'54.6" N 008°35'06.0" E
EA406	40°46'36.8" N 008°43'21.4" E
EA407	40°26'55.5" N 008°25'25.1" E
EA408	40°31'29.7" N 008°22'14.7" E
EA409	40°37'17.7" N 008°07'48.1" E