

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	RESA dimensions (m)	Description, location of arresting system	OFZ
7	8	9	10	11	12	13
see AOC	-	-	3705 x 300	240 x 150	-	Available
see AOC	-	-	3705 x 300	240 x 150	-	Available

Remarks	
14	
07	RWY shoulders: 7.5 m on each side.
25	RWY shoulders: 7.5 m on each side.

EDDS AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
07	3345	3345	3345	3045
TWY E	1400	1400	1400	NIL
TWY F	2020	2020	2020	NIL
TWY G	2210	2210	2210	NIL
TWY H	2515	2515	2515	NIL
TWY I	3090	3090	3090	NIL
TWY W	2520	2520	2520	NIL
25	3045	3045	3345	3345
TWY B	2435	2435	2735	NIL
TWY C	2175	2175	2475	NIL
TWY D	1990	1990	2290	NIL
TWY E	1665	1665	1965	NIL

Remarks	
6	
07	Nil
25	Nil

EDDS AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
07	ALSAF LIH 900 m	G LIH	3.0° 56.00 ft	W LIH	Up to 2145 m: W LIH; 2145 – 2745 m: R/W LIH; 2745 – 3045 m: R LIH 15 m spacing	Up to 2445 m: W LIH; 2455–3045 m: Y LIH. 60 m spacing	R LIH	-
25	ALSAF LIH 900 m	G LIH	3.0° 60.00 ft	W LIH	Up to 2445 m: W LIH; 2445 – 3045 m: R/W LIH; 3045 – 3345 m: R LIH 15 m spacing	Up to 2745 m: W LIH; 2745–3345 m: Y LIH. 60 m spacing	R LIH	-