

TRANSITION SEGMENTS TO ENROUTE DESCRIPTION

ARLES 1B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL100	-	RNAV1/RNP1 (1)
TF	IXORA	-	299° (302.3)	-	21.4	-	(2)	-	RNAV1/RNP1 (1)
TF	ARLES	-	299° (301.9)	-	10.5	-	(3)	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation
 (2) MCL120 or MCL150 if R83 E active
 (3) MCL180/190 depending on Geneve QNH

ARLES 1D

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LEGLO	-	-	-	-	-	+FL95	-	RNAV1/RNP1 (1)
TF	SRN	-	267° (269.8)	-	31.4	-	+FL100	-	RNAV1/RNP1 (1)
TF	IXORA	-	299° (302.3)	-	21.4	-	(2)	-	RNAV1/RNP1 (1)
TF	ARLES	-	299° (301.9)	-	10.5	-	(3)	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation
 (2) MCL120 or MCL150 if R83 E active
 (3) MCL180/190 depending on Geneve QNH

DILEB 1D

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LEGLO	-	-	-	-	-	+FL120	-	RNAV1/RNP1 (1)
TF	DILEB	-	344° (347.0)	-	20.0	-	+FL160	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

EKPAL 1S

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ILFUG	-	-	-	-	-	+TRL	-	RNAV1/RNP1 (1)
TF	TOVSA	-	178° (181.2)	-	16.9	-	+FL95	-	RNAV1/RNP1 (1)
TF	APRIV	-	152° (155.1)	-	26.6	-	+FL105	-	RNAV1/RNP1 (1)
TF	EKPAL	-	131° (134.0)	-	17.1	-	+FL195	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

EKPAL 7V

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TZO	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	ABSEM	-	223° (225.5)	-	6.4	-	-	-	RNAV1/RNP1 (1)
TF	ATGAM	-	186° (189.0)	-	4.2	-	-	-	RNAV1/RNP1 (1)
TF	TOVSA	-	151° (153.5)	-	22.0	-	+FL95	-	RNAV1/RNP1 (1)
TF	APRIV	-	152° (155.1)	-	26.6	-	+FL105	-	RNAV1/RNP1 (1)
TF	EKPAL	-	131° (134.0)	-	17.1	-	+FL195	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

GEN 1S

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ILFUG	-	-	-	-	-	+TRL	-	RNAV1/RNP1 (1)
TF	TOVSA	-	178° (181.2)	-	16.9	-	+FL95	-	RNAV1/RNP1 (1)
TF	APRIV	-	152° (155.1)	-	26.6	-	+FL105	-	RNAV1/RNP1 (1)
TF	GEN	-	243° (245.8)	-	37.4	-	-	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

LOGDI 1S

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ILFUG	-	-	-	-	-	+TRL	-	RNAV1/RNP1 (1)
TF	PABRO	-	144° (146.8)	-	26.0	-	+FL95	-	RNAV1/RNP1 (1)
TF	LOGDI	-	147° (149.6)	-	20.2	-	+FL115(2)	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

(2) MCL 95 if proceeding via T293 to LURUT

OMETO 1B

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL100	-	RNAV1/RNP1 (1)
TF	ME613	-	275° (277.8)	-	21.0		+FL150	-	RNAV1/RNP1 (1)
TF	BAVMI	-	275° (277.8)	-	5.0	-	-	-	RNAV1/RNP1 (1)
TF	OMETO	-	275° (277.5)	-	15.5	-	(2)	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation
 (2) MCL180/190 depending on Geneva QNH

OMETO 1D

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LEGLO	-	-	-	-	-	+FL95	-	RNAV1/RNP1 (1)
TF	SRN	-	267° (269.8)	-	31.4	-	+FL100	-	RNAV1/RNP1 (1)
TF	ME613	-	275° (277.8)	-	21.0		+FL150	-	RNAV1/RNP1 (1)
TF	BAVMI	-	275° (277.8)	-	5.0	-	-	-	RNAV1/RNP1 (1)
TF	OMETO	-	275° (277.5)	-	15.5	-	(2)	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation
 (2) MCL180/190 depending on Geneva QNH

OSKOR 1F

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LEGLO	-	-	-	-	-	+FL95	-	RNAV1/RNP1 (1)
TF	OSKOR	-	087° (090.2)	-	14.6	-	+FL125(2)	-	RNAV1/RNP1 (1)

- (1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation
 (2) MCL 110 if proceeding via L615

PEPAG 1D

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	LEGLO	-	-	-	-	-	+FL95	-	RNAV1/RNP1 (1)
TF	ME612	-	298° (301.1)	-	11.8	-	+FL130	-	RNAV1/RNP1 (1)
TF	OSVIC	-	303° (306.2)	-	7.2	-	+FL140	-	RNAV1/RNP1 (1)
TF	PEPAG	-	303° (306.1)	-	16.5	-	(2)	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

(2) MCL140/150 depending on Zurich QNH

VOG 1S

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ILFUG	-	-	-	-	-	+TRL	-	RNAV1/RNP1 (1)
TF	TOVSA	-	178° (181.2)	-	16.9	-	+FL95	-	RNAV1/RNP1 (1)
TF	VOG	-	252° (255.4)	-	28.3	-	+FL100	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

VOG 7U

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TZO	-	-	-	-	-	+6000	-	RNAV1/RNP1 (1)
TF	ABSEM	-	223° (225.5)	-	6.4	-	-	-	RNAV1/RNP1 (1)
TF	VOG	-	207° (210.4)	-	36.0	-	+FL100	-	RNAV1/RNP1 (1)

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

WAYPOINT LIST

Waypoint Identifier	Coordinates
ME612	45°45'06.86" N 009°31'41.17" E
ME613	45°41'33.57" N 008°31'36.41" E