

STAR RNAV 1/ RNP 1 RWY 30 DESCRIPTION

AMLON 2E

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	AMLON	-	-	-	-	-	-	-	RNAV1/RNP1 (4)
TF	PR531	-	177 (180.5)	-	15.3	-	+6000	-	RNAV1/RNP1 (4)
TF	PR526	-	177 (180.5)	-	5.2	-	-	-210	RNAV1/RNP1 (4)
TF	PR519	-	124 (127.9)	-	5.6	-	-	-210	RNAV1/RNP1 (4)
TF	ROGAK	-	214 (217.8)	-	5.0	R	+3000	-185	RNAV1/RNP1 (4)

ANC 2E

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ANC	-	-	-	-	-	-	-	RNAV1/RNP1 (4)
TF	PR533	-	288 (291.4)	-	19.1	-	+FL 120 (5)	-230	RNAV1/RNP1 (4)
TF	EGHOS	-	300 (303.4)	-	10.4	-	+4000	-210	RNAV1/RNP1 (4)
TF	ROGAK	-	017 (020.3)	-	5.0	R	+3000	-185	RNAV1/RNP1 (4)

ANC 2X

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ANC	-	-	-	-	-	-	-	RNAV1/RNP1 (4)
TF	PR524	-	302 (305.2)	-	18.2	-	+FL 120 (5)	-230	RNAV1/RNP1 (4)
TF	ROGAK	-	301 (304.9)	-	12.0	-	+3000	-185	RNAV1/RNP1 (4)

ASDOR 3E

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ASDOR	-	-	-	-	-	-	-	RNAV1/RNP1 (4)
TF	PR529	-	073 (076.6)	-	10.0	-	+FL 100	-	RNAV1/RNP1 (4)
TF	PR527	-	073 (076.8)	-	3.4	-	-	-210	RNAV1/RNP1 (4)
TF	EGHOS	-	105 (108.3)	-	7.5	-	+4000	-210	RNAV1/RNP1 (4)
TF	ROGAK	-	017 (020.3)	-	5.0	L	+3000	-185	RNAV1/RNP1 (4)

BAGNO 3E

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	BAGNO	-	-	-	-	-	-	-	RNAV1/RNP1 (4)
TF	PR553	-	091 (094.5)	-	12.5	-	+FL 110	-	RNAV1/RNP1 (4)
TF	PR532	-	091 (094.7)	-	21.4	-	TRL	-	RNAV1/RNP1 (4)
TF	PR527	-	092 (095.0)	-	5.2	-	-	-210	RNAV1/RNP1 (4)
TF	EGHOS	-	105 (108.3)	-	7.5	-	+4000	-210	RNAV1/RNP1 (4)
TF	ROGAK	-	017 (020.3)	-	5.0	L	+3000	-185	RNAV1/RNP1 (4)

HOLDING RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	EGHOS	105 (108.4)	3.6	-/4.4	R	+4000	-	-185	+3.4	RNAV 1
HM	ROGAK	309 (312.4)	3.4	-/4.3	R	+3000	+5000 (3)	-185	+3.4	RNAV 1

REMARKS:

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

(3) Higher altitude/level ATC discretion.

(4) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation

(5) + 5000 FT ATC Discretion

WAYPOINT LIST

Waypoint Identifier	Coordinates
PR519	43°56'26.35"N - 012°58'24.65"E
PR524	43°45'38.57"N - 013°07'44.40"E
PR526	43°59'50.84"N - 012°52'19.67"E
PR527	43°50'09.13"N - 012°41'57.51"E
PR529	43°49'22.53"N - 012°37'22.82"E
PR531	44°05'04.42"N - 012°52'23.56"E
PR532	43°50'36.60"N - 012°34'51.04"E
PR533	43°42'06.09"N - 013°03'43.68"E
PR553	43°52'25.78"N - 012°05'21.83"E