

BIKF RNAV STAR RWY 01
Recommended Coding Tables

DEVUD 5N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	DEVUD	-		+11.3					RNAV 1 (GNSS)
020	TF	KF301	-	230 (218.8)	+11.4	6.2		F160-		RNAV 1 (GNSS)
030	TF	KF102	-	230 (218.7)	+11.4	8.3		F150-		RNAV 1 (GNSS)
040	TF	KF103	-	230 (218.5)	+11.5	7.0		F110+		RNAV 1 (GNSS)
050	TF	ABEXI	-	230 (218.4)	+11.6	8.9		F130- F100+		RNAV 1 (GNSS)
060	TF	KF384	-	272 (260.0)	+11.7	10.0		F110-		RNAV 1 (GNSS)
070	TF	KF385	-	271 (259.7)	+11.8	5.0		A7000+		RNAV 1 (GNSS)
080	TF	KOPUM	-	271 (259.5)	+12.0	10.5		A7000-		RNAV 1 (GNSS)
090	TF	DEXON	-	263 (251.2)	+12.1	7.9		A3500+	-230	RNAV 1 (GNSS)

NASBU 5N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	NASBU	-		+11.2					RNAV 1 (GNSS)
020	TF	ABEXI	-	272 (260.8)	+11.6	21.7		F130- F100+		RNAV 1 (GNSS)
030	TF	KF384	-	272 (260.0)	+11.7	10.0		F110-		RNAV 1 (GNSS)
040	TF	KF385	-	271 (259.7)	+11.8	5.0		A7000+		RNAV 1 (GNSS)
050	TF	KOPUM	-	271 (259.5)	+12.0	10.5		A7000-		RNAV 1 (GNSS)
060	TF	DEXON	-	263 (251.2)	+12.1	7.9		A3500+	-230	RNAV 1 (GNSS)

ASRUN 4N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	ASRUN	-		+11.1					RNAV 1 (GNSS)
020	TF	TIMLU	-	297 (285.5)	+11.5	16.3		F100+		RNAV 1 (GNSS)
030	TF	KF113	-	296 (284.9)	+11.7	10.9		F120-		RNAV 1 (GNSS)
040	TF	KF379	-	296 (284.7)	+12.0	15.1		A7000-		RNAV 1 (GNSS)
050	TF	DEXON	-	296 (284.2)	+12.1	7.5		A3500+	-230	RNAV 1 (GNSS)

BASLU 4N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	BASLU	-		+11.4					RNAV 1 (GNSS)
020	TF	ELSIG	-	331 (319.9)	+11.6	14.0				RNAV 1 (GNSS)
030	TF	KF386	-	331 (319.6)	+11.8	14.2		F120-		RNAV 1 (GNSS)
040	TF	KF387	-	331 (319.3)	+11.9	6.0		F100-		RNAV 1 (GNSS)
050	TF	KF388	-	331 (319.2)	+12.0	5.7		A7000-		RNAV 1 (GNSS)
060	TF	DEXON	-	331 (319.1)	+12.1	6.0		A3500+	-230	RNAV 1 (GNSS)

BIRNA 3N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	BIRNA	-		+13.0					RNAV 1 (GNSS)
020	TF	UMTAL	-	069 (056.1)	+12.8	14.3				RNAV 1 (GNSS)
030	TF	RENDU	-	069 (056.5)	+12.4	33.4		A3500+	-230	RNAV 1 (GNSS)

ELDIS 4N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	ELDIS	-		+13.3					RNAV 1 (GNSS)
020	TF	VIBER	-	096 (083.0)	+13.0	18.4				RNAV 1 (GNSS)
030	TF	RENDU	-	097 (083.6)	+12.4	33.4		A3500+	-230	RNAV 1 (GNSS)

GIRUG 4N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	GIRUG	-		+13.6					RNAV 1 (GNSS)
020	TF	RIKUG	-	123 (109.8)	+13.1	24.4				RNAV 1 (GNSS)
030	TF	RENDU	-	124 (111.3)	+12.4	33.4		A3500+	-230	RNAV 1 (GNSS)

INGAN 6N

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course / Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt/h)	Navigation Specification
010	IF	INGAN	-		+13.6					RNAV 1 (GNSS)
020	TF	NIZOL	-	134 (120.3)	+12.9	34.1				RNAV 1 (GNSS)
030	TF	RENDU	-	168 (155.0)	+12.4	33.4		A3500+	-230	RNAV 1 (GNSS)