

SID DESCRIPTION**ESINO 7H**

Proceed via SOSAK (RDL 215 OST VOR) – TORLI – ESINO.

MCA/MCL: TORLI 3000 FT; ESINO FL 90 (if proceeding via M126), FL 100 (if proceeding via Z924 or M738)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	TORLI	-	215 (218.3)	-	1.9	-	+3000	-	Conventional/ RNAV1
TF	ESINO	-	215 (218.3)	-	16.0	-	(*)	-	Conventional/ RNAV1

(*) FL90 if proceeding via M126; FL100 if proceeding via Z924 or M738

KONUT 8A

Proceed via SOSAK - TORLI, then turn left on TR 177° bound to KONUT.

MCA/MCL: TORLI 3000 FT; KONUT FL 100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	TORLI	-	215 (218.3)	-	1.9	-	+3000	-	Conventional/ RNAV1
TF	KONUT	-	177 (180.3)	-	18.2	-	+FL100	-	Conventional/ RNAV1

PEPIX 9A

Proceed via XIBRI – ELVIN (RDL 187 OST VOR) until 27 NM OST DME, then turn left until joining RDL 159 TAQ VOR bound to PEPIX.

MCA/MCL: ELVIN 3000 FT; PEPIX FL 100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	ELVIN	-	187 (190.4)	-	3.9	-	+3000	-	Conventional/ RNAV1
TF	ADMOP	-	187 (190.4)	-	10.5	-	-	-	Conventional/ RNAV1
TF	PEPIX	-	159 (162.2)	-	10.2	-	+FL100	-	Conventional/ RNAV1

PEPIX 9B

Proceed via SOSAK (RDL 215 OST VOR) - TORLI then turn left on TR 177° to KONUT, then turn left to join and follow RNAV route L50 bound to PEPHX.

MCA/MCL: TORLI 3000 FT; KONUT FL 100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	TORLI	-	215 (218.3)	-	1.9	-	+3000	-	Conventional/ RNAV1
TF	KONUT	-	177 (180.3)	-	18.2	-	+FL100	-	Conventional/ RNAV1
TF	PEPIX	-	133 (135.7)	-	11.1	-	+FL100	-	Conventional/ RNAV1

RIFFI 9G

Proceed via XIBRI (RDL 187 OST VOR) – ELVIN then turn left on TR 131° (RDL 311 PNZ VOR) bound to RIFFI.

MCA/MCL: ELVIN 3000 FT; RIFFI FL 90

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	ELVIN	-	187 (190.4)	-	3.9	-	+3000	-	Conventional/ RNAV1
TF	RIFFI	-	131 (134.0)	-	23.3	-	+FL90	-	Conventional/ RNAV1

RIFFI 9H

On SOSAK turn left (IAS MAX 210KT) on TR 131° (RDL 311 PNZ VOR) bound to RIFFI.

MCA/MCL: SOSAK 3000 FT; RIFFI FL 90

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	-	-	-	-	-	+3000		Conventional/ RNAV1
TF	TORLI	-	215 (218.3)	-	1.9	-	-	-210	Conventional/ RNAV1
TF	RIFFI	-	131 (134.0)	-	32.2	-	+FL90	-	Conventional/ RNAV1

ROTUN 8A

Proceed via XIBRI – ELVIN (RDL 187 OST VOR) until 27 NM OST DME, then turn left until joining RDL 159 TAQ VOR bound to PEPIX then ROTUN.

MCA/MCL: ELVIN 3000 FT; PEPIX FL 100; ROTUN FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	XIBRI	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	ELVIN	-	187 (190.4)	-	3.9	-	+3000	-	Conventional/ RNAV1
TF	ADMOP	-	187 (190.4)	-	10.5	-	-	-	Conventional/ RNAV1
TF	PEPIX	-	159 (162.2)	-	10.2	-	+FL100		Conventional/ RNAV1
TF	ROTUN	-	159 (162.3)	-	17.5	-	+FL110		Conventional/ RNAV1

ROTUN 8B

Proceed via SOSAK (RDL 215 OST VOR) - TORLI, then turn left on TR 177° to KONUT, then turn left to join and follow RNAV route L50 to PEPIX then turn right on TR 159° (RDL 159 TAQ VOR) bound to ROTUN.

MCA/MCL: TORLI 3000 FT; KONUT FL 100; ROTUN FL 110

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SOSAK	-	-	-	-	-	-	-	Conventional/ RNAV1
TF	TORLI	-	215 (218.3)	-	1.9	-	+3000	-	Conventional/ RNAV1
TF	KONUT	-	177 (180.3)	-	18.2	-	+FL100	-	Conventional/ RNAV1
TF	PEPIX	-	133 (135.7)	-	11.1	-	+FL100		Conventional/ RNAV1
TF	ROTUN	-	159 (162.3)	-	17.5	-	+FL110		Conventional/ RNAV1