

EDDR AD 2.13 Declared distances

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)
1	2	3	4	5
09 TWY B	1900 889	2000 989	1900 889	1840 NIL
27 TWY B	1930 985	1990 1045	1930 985	1840 NIL

Remarks	
6	
09	Nil
27	Nil

EDDR AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
09	SALS LIH 240 m Sequence flash available	G LIH	3.2° 52.00 ft	-	Up to 1320 m: W LIH 1320 – 1620 m: R/W LIH 1620 – 1974 m: R LIH. 15 m spacing	W LIH	R LIL	-
27	ALSAF LIH 900 m Sequence flash available	G LIH	3.0° 52.00 ft	-	Up to 1320 m: W LIH 1320 – 1620 m: R/W LIH 1620 – 1974 m: R LIH. 15 m spacing	W LIH	R LIL	-

Remarks	
10	
09	Nil
27	Nil

EDDR AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	ABN white/white on TWR at night, O/R during the day
2	LDI location and LGT Anemometer location and LGT	See Chart AD 2 EDDR 2-5
3	TWY edge and centre line LGT	TWY edge lights of TWYs: B LIL
4	Secondary power supply including switch-over time	Available/<1 SEC
5	Remarks	Nil