

MUENCHEN
RNP RWY 08L

INSTRUMENT APPROACH PROCEDURE
TABULAR DESCRIPTION

Procedure Remarks												
1.	WHEN RWY VACATED, CONTACT GROUND.											
2.	* OPERATIONAL FL.											
3.	BARO-VNAV OPERATIONS NOT AUTHORIZED BELOW -15°C.											
4.	EGNOS CHANNEL 87870 E08A											

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from MIQ	IF	MIQ	N 48 34 12.81 E 011 35 51.01	-	-	-	-	A5000+	-	-	RNP APCH	-
	TF	DM421	N 48 24 49.23 E 011 19 52.01	-	(T228.6) 226	14.2	-	-	-	-	RNP APCH	-
	TF	DM431	N 48 19 46.10 E 011 20 47.36	-	(T173.1) 170	5.1	-	-	-	-	RNP APCH	-
APCH	TF	MAGAT	N 48 20 29.48 E 011 29 47.18	-	(T083.1) 080	6.1	-	A5000+	-	-	RNP APCH	-
	TF	RW08L	N 48 21 45.96 E 011 46 03.18	Y	(T083.2) 080	10.9	-	-	-	-3.00 / 50	RNP APCH	-
Missed APCH	CF	DM551	N 48 22 00.19 E 011 49 08.30	Y	(T083.4) 080	2.1	-	-	-	-	RNP APCH	-
	CA	-	-	-	(T083.4) 080	-	-	A1900+	-	-	RNP APCH	-
	DF	MIQ	N 48 34 12.81 E 011 35 51.01	-	-	-	L	@A5000	-	-	RNP APCH	-

RNAV HOLDING IDENTIFICATION								
Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	MIQ	N 48 34 12.81 E 011 35 51.01	(T083.1) 080	230-	A5000+	1 min	R	-