

## TABULAR DESCRIPTION RNAV 1 SID RWY 09R VOBL:-

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course/Heading °M(°T)	Turn Direction	Altitude (ft)	Speed Limit (Kt)	Distance/ Time NM/Min	VA °	Navigation Specification
<b>VEMBO 8C</b>										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	DF	BL763				+FL090	-250.00			RNAV 1
30	TF	BL777		019.77° Mag / 017.94° True		-FL110		11.50		RNAV 1
40	TF	VEMBO		075.82° Mag / 073.99° True				48.25		RNAV 1
<b>ANIRO 8C</b>										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	DF	BL763				+FL090	-250.00			RNAV 1
30	TF	BL777		019.77° Mag / 017.94° True		-FL110		11.50		RNAV 1
40	TF	ANIRO		041.63° Mag / 039.80° True				51.82		RNAV 1
<b>TULNA 8C</b>										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	DF	BL763				+FL090	-250.00			RNAV 1
30	TF	BL764		092.39° Mag / 090.56° True				6.50		RNAV 1
40	TF	TULNA		104.17° Mag / 102.34° True				60.28		RNAV 1
<b>LATID 8C</b>										
10	VA			092.34° Mag / 090.51° True		+3400	-250.00		4.00	RNAV 1
20	DF	BL761				+7000	-250.00			RNAV 1
30	TF	BL701		002.38° Mag / 0.55° True			-250.00	8.04		RNAV 1
40	TF	BL406		331.58° Mag / 329.75° True		-FL110		14.03		RNAV 1
50	TF	BL779		010.51° Mag / 008.68° True				9.80		RNAV 1
60	TF	LATID		010.52° Mag / 008.69° True				47.69		RNAV 1
<b>SAI 8C</b>										
10	VA			092.34° Mag / 090.51° True	-	+3400	-250.00		4.00	RNAV 1
20	DF	BL761			-	+7000	-250.00			RNAV 1
30	TF	BL701	N	002.38° Mag / 0.55° True	-		-250.00	8.04		RNAV 1
40	TF	BL406	N	331.58° Mag / 329.75° True	-	-FL110		14.03		RNAV 1
50	TF	BL779	N	010.51° Mag / 008.68° True	-			9.80		RNAV 1
60	TF	SAI	N	356.97° Mag / 355.14° True	-			27.74		RNAV 1
<b>VAGPU 8C</b>										
10	VA			092.34° Mag / 090.51° True		+3400	250.00		4.00	RNAV 1