

General Remarks	
1.	ATTENTION DEPARTING AIRCRAFT SIMULTANEOUS PARALLEL DEPARTURES IN PROGRESS. PILOTS HAVE TO PROCEED EXACTLY ON EXTENDED CENTERLINE UNTIL STARTING TURNS AS PUBLISHED IN DEPARTURE ROUTES AND SHALL REMAIN ON TWR FREQUENCY UNTIL FURTHER ADVISED.
2.	RWY 08R IS TO BE USED ESPECIALLY FOR DEPARTURES TO SW, S, SE and E.
3.	1. RNAV-1 or RNP-1 or A-RNP equivalent. 2. GPS required. 3. DME/DME, DME/DME/IRU not authorized.

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
ANKER 9E	ANKER NINE ECHO Climb on course 080° to DM083; LT, to ANKER (△). MAX IAS 230 kt until DM083. MAX IAS 250 kt until ANKER.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!				
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CA	-	-	-	(T083.3) 080	-	-	A1900+	-	RNAV 1	-
CF	DM083	N 48 21 33.45 E 011 59 48.40	-	(T083.3) 080	-	-	-	230-	RNAV 1	-
TF	ANKER	N 48 34 21.45 E 012 00 08.38	-	(T001.0) 358	12.8	-	-	250-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
EVIVA 4E	EVIVA FOUR ECHO Climb on course 080° to DM084; or 1900, whichever is later; LT, course 357° to DM088; LT, to DM089; LT, to EVIVA (△). MAX IAS 250 kt until DM089.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!		PDG 4.4% (265 FT/NM) until passing 1900 due to noise abatement.		
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM084	N 48 20 51.77 E 011 50 30.98	Y	(T083.3) 080	1.5	-	-	-	RNAV 1	-
CA	-	-	-	(T083.3) 080	-	-	A1900+	-	RNAV 1	-
CF	DM088	N 48 27 33.00 E 011 52 44.97	-	(T360.0) 357	-	L	-	-	RNAV 1	-
TF	DM089	N 48 34 59.25 E 011 49 40.26	-	(T344.6) 342	7.7	-	-	250-	RNAV 1	-
TF	EVIVA	N 48 40 02.75 E 011 42 10.58	-	(T315.6) 313	7.1	-	-	-	RNAV 1	-

Designator	Route			After Take-Off				Procedure Remarks/ Procedure Timesheet		
				Climb to		Contact				
INPUD 3E	INPUD THREE ECHO Climb on course 080° to DM084; or 1900, whichever is later; LT, direct to DM076; to DM065; RT, to INPUD (△). MAX IAS 250 kt until DM065.			FL 070		MUENCHEN RADAR 123.905 WHEN ADVISED BY TOWER!		PDG 4.4% (265 FT/NM) until passing 1900 due to noise abatement.		
Recommen- ded Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	NAV- Specification	Remarks
CF	DM084	N 48 20 51.77 E 011 50 30.98	Y	(T083.3) 080	1.5	-	-	-	RNAV 1	-
CA	-	-	-	(T083.3) 080	-	-	A1900+	-	RNAV 1	-
DF	DM076	N 48 23 48.53 E 011 51 57.92	-	-	-	L	-	-	RNAV 1	-
TF	DM065	N 48 34 12.81 E 011 35 51.01	-	(T314.3) 311	14.9	-	-	250-	RNAV 1	-
TF	INPUD	N 48 40 01.57 E 011 32 29.37	-	(T339.0) 336	6.2	-	-	-	RNAV 1	-