

**TRANSITION SEGMENT TO ENROUTES RWY 35 DESCRIPTION****ARLES 2A**

SRN VOR proceed on TR 300° (RDL 300 SRN VOR) to IXORA (INT RDL 300/21 NM SRN VOR/DME) direct to ARLES (INT RDL/32 NM SRN VOR/DME).

MCL: IXORA, FL120 (FL 145 if R 83 E is active); ARLES, FL180/190 depending on Geneve QNH

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL85	-	RNAV1
TF	IXORA	-	300° (302.3)	-	21.5	-	+FL120 (1)	-	RNAV1
TF	ARLES	-	299° (301.9)	-	10.6	-	+FL180 (2)	-	RNAV1

(1) FL145 if R83 E is active

(2) FL180/190 depending on Geneve QNH

**DEVOX 6B (ATC discretion)**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TOVSA	-	-	-	-	-	-	-	RNAV1
TF	ML401	-	235° (238.0)	-	12.7	-	+FL100	-	RNAV1
TF	DEVOX	-	235° (237.8)	-	31.1	-	-	-	RNAV1

**EKPAL 6A**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TOVSA	-	-	-	-	-	-	-	RNAV1
TF	APRIV	-	152° (155.1)	-	26.6	-	+FL100	-	RNAV1
TF	EKPAL	-	131° (134.0)	-	17.1	-	+FL 195	-	RNAV1

**ELTAR 6B**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	RUVAB	-	-	-	-	-	-	-	RNAV1
TF	EKBUV	-	083° (085.6)	-	23.1	-	+FL110	-	RNAV1
TF	ELTAR	-	108° (111.5)	-	23.1	-	-	-	RNAV1

**GEN 6Q**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TOVSA	-	-	-	-	-	-	-	RNAV1
TF	APRIV	-	152° (155.1)	-	26.6	-	+FL100	-	RNAV1
TF	GEN	-	243° (245.8)	-	37.4	-	-	-	RNAV1

**GEN 7V (ATC discretion)**

TOVSA proceed on TR 207° (RDL 027 GEN VOR) via ML402 (INT RDL 027 / 34 NM GEN VOR/DME) direct to GEN VOR/DME.

MCL: ML402, FL100

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	TOVSA	-	-	-	-	-	-	-	RNAV1
TF	ML402	-	207° (210.0)	-	11.7	-	+FL100	-	RNAV1
TF	GEN	-	207° (209.9)	-	34.0	-	-	-	RNAV1

**LAGEN 5A (ATC discretion)**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL85	-	RNAV1
TF	MMP	-	266° (268.6)	-	12.1	-	-	-	RNAV1
TF	FARAK	-	244° (246.8)	-	13.1	-	-	-	RNAV1
TF	TONDA	-	197° (199.2)	-	28.3	-	-	-	RNAV1
TF	LAGEN	-	162° (164.9)	-	44.4	-	+FL 110	-	RNAV1

**LOGDI 7A**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ABSEM	-	-	-	-	-	-	-	RNAV1
TF	ML403	-	121° (123.9)	-	5.8	-	+5000FT	-	RNAV1
TF	TUVIB	-	121° (123.9)	-	5.8	-	+6000 FT	-	RNAV1
TF	LOGDI	-	145° (148.4)	-	46.7	-	+FL115 (1)	-	RNAV1

(1) FL 95 if proceeding via T293 to LURUT

**NEDED 5A (ATC discretion)**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL85	-	RNAV1
TF	MMP	-	266° (268.6)	-	12.1	-	-	-	RNAV1
TF	FARAK	-	244° (246.8)	-	13.1	-	-	-	RNAV1
TF	TONDA	-	197° (199.2)	-	28.3	-	-	-	RNAV1
TF	NEDED	-	186° (188.7)	-	25.2	-	+FL 200	-	RNAV1

**NESTI 6A**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	RUVAB	-	-	-	-	-	-	-	RNAV1
TF	EKBUV	-	083° (085.6)	-	23.1	-	+FL120	-	RNAV1
TF	NESTI	-	083° (086.2)	-	13.0	-	+FL135	-	RNAV1

**OMETO 6A**

SRN VOR proceed on TR 275° (RDL 275 SRN VOR) via BAVMI (INT RDL 275/26 NM SRN VOR/DME) direct to OMETO (INT RDL 275/41 NM SRN VOR/DME).

MCL: BAVMI, FL150; OMETO, FL180/190 depending on Geneve QNH

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	SRN	-	-	-	-	-	+FL85	-	RNAV1
TF	BAVMI	-	275° (277.8)	-	26.1	-	+FL150	-	RNAV1
TF	OMETO	-	275° (277.5)	-	15.5	-	+FL180(1)	-	RNAV1

(1) FL180/190 depending on Geneve QNH

**OSKOR 8B (ATC discretion) (1)**

TZO VOR proceed on TR 075° (RDL 075 TZO VOR) then continue to OSKOR (INT RDL 075/26 NM TZO VOR/DME).

MCL: RDL 075/15 NM TZO VOR/DME, FL95; OSKOR, FL125 (or FL110 if proceeding via AWY L615)

(1) Compulsory only for turbo propeller aircraft or no RNAV equipped

**OSKOR 6D (ATC discretion)**

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
IF	ABSEM	-	-	-	-	-	-	-	RNAV1
TF	ML403	-	121° (123.9)	-	5.8	-	+5000FT	-	RNAV1
TF	TUVIB	-	121° (123.9)	-	5.8	-	+6000 FT	-	RNAV1
TF	ELBOD	-	079° (082.0)	-	7.8	-	+FL85	-	RNAV1
TF	VAKON	-	056° (058.4)	-	9.6	-	+FL105	-	RNAV1
TF	OSKOR	-	023° (025.6)	-	11.4	-	+FL125 (1)	-	RNAV1

(1) FL 110 if proceeding via AWY L615

**PEPAG 1B (ATC Discretion) (2)**

TZO VOR proceed on TR039° (RDL 039 TZO VOR) to OLPUR (INT. RDL 039/07 NM TZO VOR/DME), then turn left to join and follow RDL 303 BRL VOR and proceed to OSVIC (INT. RDL 303/15 NM BRL VOR/DME) then continue to PEPAG (INT RDL 303/32 BRL VOR/DME).

MCA/MCL: RDL303/8 NM BRL VOR/DME, MCL 120; RDL303/11 NM BRL VOR/DME, MCL 130;  
RDL303/15 NM BRL VOR/DME, MCL 140; PEPAG, FL140/150 depending on Zurich QNH.

(2) Compulsory only for turbo propeller aircraft or no RNAV equipped

**WAYPOINT LIST**

Waypoint Identifier	Coordinates
ML401	44°58'24.86" N 009°21'42.85" E
ML402	44°54'59.54" N 009°28'35.90" E
ML403	45°25'49.20" N 009°30'40.39" E