

EDTD AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
18	-	W LIH	-	-	-	W LIL_LIH	R LIH	-
36	LIL_LIH	W LIH	-	-	-	W LIL_LIH	R LIH	-

Remarks	
	10
18	Nil
36	Nil

EDTD AD 2.15 Other lighting, secondary power supply

1	ABN/IBN location, characteristics and hours of operation	White/white on TWR
2	LDI location and LGT Anemometer location and LGT	140 m W of RWY
3	TWY edge and centre line LGT	TWY edge lights of TWY B: B LIL
4	Secondary power supply including switch-over time	Available
5	Remarks	Nil

EDTD AD 2.16 Helicopter landing area

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation m/ft	NIL
3	TLOF and FATO area dimensions, surface type, bearing strength and marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	Not specified, according to direction from TWR

EDTD AD 2.17 ATS airspace

1	Designation and lateral limits	RMZ
2	Vertical limits	1000 ft AGL
3	Airspace classification	G
4	ATS unit call sign Language(s)	DONAUESCHINGEN INFORMATION English, German
5	Transition altitude	5000 ft MSL
6	Hours of applicability	NIL
7	Remarks	For detailed airspace description see ENR 2.2