

**SID RNAV 1 RWY 22 L/R
VENEZIA/Tessera**

REMARK

Minimum climb gradient:

- 7.5% (455 FT/NM) until passing FL 90 for SIDs ROSKA 6Q, CHI 6Q, VIC 6Q and ROKIB 6Q;
- 7.0 % (425 FT/NM) for SIDs CHI 6R and ROSKA 6R.

CHI 6Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ534	-	219 (222.1)	-	5.5	-	+4000	210	RNAV1
TF	PZ612	-	309 (312.0)	-	4.5	R	-	210	RNAV1
TF	PZ613	-	036 (039.2)	-	3.0	R	-	210	RNAV1
TF	PZ488	-	064 (067.2)	-	11.2	-	+FL90	-	RNAV1
TF	PZ489	-	095 (098.1)	-	6.3	-	-	-	RNAV1
TF	AKADO	-	186 (189.5)	-	11.5	R	-	-	RNAV1
TF	CHI	-	207 (210.6)	-	18.3	-	-	-	RNAV1

CHI 6R (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ611	-	166 (169.7)	-	6.2	-	+4000	-	RNAV1
TF	CHI	-	179 (182.7)	-	16.4	-	+6000	-	RNAV1

ROKIB 6Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ534	-	219 (222.1)	-	5.5	-	+4000	210	RNAV1
TF	PZ612	-	309 (312.0)	-	4.5	R	-	210	RNAV1
TF	PZ614	-	242 (245.0)	-	7.0	L	+FL90	-	RNAV1
TF	PZ615	-	319 (322.8)	-	6.3	-	-	-	RNAV1
TF	ARLUK	-	352 (355.5)	-	15.8	-	+FL110	-	RNAV1
TF	PZ485	Y	331 (334.3)	-	9.0	-	+FL130	-	RNAV1
TF	ROKIB	-	331 (334.3)	-	5.0	-	+FL140	-	RNAV1

ROSKA 6Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ534	-	219 (222.1)	-	5.5	-	+4000	210	RNAV1
TF	PZ612	-	309 (312.0)	-	4.5	R	-	210	RNAV1
TF	PZ613	-	036 (039.2)	-	3.0	R	-	210	RNAV1
TF	PZ488	-	064 (067.2)	-	11.2	-	+FL90	-	RNAV1
TF	PZ489	-	095 (098.1)	-	6.3	-	-	-	RNAV1
TF	ROSKA	-	129 (132.9)	-	18.3	-	-	-	RNAV1

ROSKA 6R (ATC Discretion)

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ611	-	166 (169.7)	-	6.2	-	+4000	-	RNAV1
TF	AKADO	-	091 (094.1)	-	8.5	-	+6000	-	RNAV1
TF	ROSKA	-	091 (094.2)	-	15.3	-	+FL90	-	RNAV1

VIC 6Q

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	219 (222.1)	-	-	-	+410	-	RNAV1
DF	PZ610	-	-	-	-	-	-	-	RNAV1
TF	PZ534	-	219 (222.1)	-	5.5	-	+4000	210	RNAV1
TF	PZ612	-	309 (312.0)	-	4.5	R	-	210	RNAV1
TF	PZ614	-	242 (245.0)	-	7.0	L	+FL90	-	RNAV1
TF	PZ615	-	319 (322.8)	-	6.3	-	-	-	RNAV1
TF	VIC	-	319 (322.8)	-	13.5	-	+FL120	-	RNAV1

WAYPOINT LIST

Waypoint Identifier	Coordinates
PZ485	45°51'37.9" N 011°44'38.7" E
PZ488	45°32'14.7" N 012°23'49.3" E
PZ489	45°31'20.6" N 012°32'41.7" E
PZ534	45°22'34.9" N 012°11'12.5" E
PZ610	45°26'40.8" N 012°16'27.2" E
PZ611	45°20'36.6" N 012°18'00.4" E
PZ612	45°25'35.4" N 012°06'27.6" E
PZ613	45°27'55.8" N 012°09'10.3" E
PZ614	45°22'37.6" N 011°57'27.8" E
PZ615	45°27'37.4" N 011°52'04.9" E