

SID RNAV 1/RNP 1 RWY 30 DESCRIPTION**NOISE ABATEMENT PROCEDURES RWY 30**

See AD 2 Table 21 "NOISE ABATEMENT PROCEDURES"

REMARKS

Minimum Climb Gradient: 6.5% (392 FT/NM) to 6000 Ft for SID EKTUK 6N, PELEG 6P/6T.

Minimum Climb Gradient: 6.7% (407 FT/NM) to 6000 Ft for SID AMLON 6N and ANC 6N.

AMLON 6N

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	291 (294.0)	+3.4	-	-	+430	-210	RNAV1/RNP1 (1)
CF	PR604	Y	291 (294.0)	+3.4	3.7	-	+1500	-210	RNAV1/RNP1 (1)
TF	PR613	-	021 (023.9)	-	9.6	-	+6000	-210	RNAV1/RNP1 (1)
TF	PR618	-	051 (054.7)	-	4.9	-	-	-	RNAV1/RNP1 (1)
TF	AMLON	-	051 (054.8)	-	9.4	-	+ FL 85	-	RNAV1/RNP1 (1)

ANC 6N

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	291 (294.0)	+3.4	-	-	+430	-210	RNAV1/RNP1 (1)
CF	PR604	Y	291 (294.0)	+3.4	3.7	-	+1500	-210	RNAV1/RNP1 (1)
DF	PR611	-	-	-	-	R	-	-210	RNAV1/RNP1 (1)
TF	PR623	-	124 (127.4)	-	13.7	-	-	-	RNAV1/RNP1 (1)
TF	PR524	-	136 (139.3)	-	17.9	-	+FL120	-	RNAV1/RNP1 (1)
TF	ANC	-	121 (124.9)	-	18.2	-	-	-	RNAV1/RNP1 (1)

EKTUK 6N

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	291 (294.0)	+3.4	-	-	+430	-210	RNAV1/RNP1 (1)
CF	PR604	Y	291 (294.0)	+3.4	3.7	-	+1500	-210	RNAV1/RNP1 (1)
TF	PR616	-	264 (267.4)	-	11.0	-	+5800	-	RNAV1/RNP1 (1)
TF	EKTUK	-	264 (267.2)	-	15.0	-	+FL95	-	RNAV1/RNP1 (1)

PELEG 6P

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	291 (294.0)	+3.4	-	-	+430	-210	RNAV1/RNP1 (1)
CF	PR604	Y	291 (294.0)	+3.4	3.7	-	+1500	-210	RNAV1/RNP1 (1)
TF	PR609	-	284 (287.3)	-	6.0	-	-	-	RNAV1/RNP1 (1)
TF	PR614	-	284 (287.2)	-	5.0	-	+5800	-	RNAV1/RNP1 (1)
TF	PELEG	-	284 (287.2)	-	24.3	-	+FL95	-	RNAV1/RNP1 (1)

PELEG 6T

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	291 (294.0)	+3.4	-	-	+430	-210	RNAV1/RNP1 (1)
CF	PR604	Y	291 (294.0)	+3.4	3.7	-	+1500	-210	RNAV1/RNP1 (1)
TF	PR616	-	264 (267.4)	-	11.0	-	+5800	-	RNAV1/RNP1 (1)
TF	EKTUK	-	264 (267.2)	-	15.0	-	+FL 95	-	RNAV1/RNP1 (1)
TF	PELEG	-	323 (326.4)	-	14.0	-	-	-	RNAV1/RNP1 (1)

REMARK:

(1) For "monitoring and alerting" reasons, RNP1 specification is required in case of radar service unavailability or degradation.

WAYPOINT LIST

Waypoint Identifier	Coordinates
PR524	43°45'38.57" N - 013°07'44.40" E
PR604	44°03'20.01" N - 012°30'55.16" E
PR609	44°05'06.92" N - 012°22'58.33" E
PR611	44°07'33.00" N - 012°36'36.75" E
PR613	44°12'07.44" N - 012°36'20.84" E
PR614	44°06'35.58" N - 012°16'20.62" E
PR616	44°02'48.87" N - 012°15'41.00" E
PR618	44°14'55.82" N - 012°41'52.15" E
PR623	43°59'12.83" N - 012°51'37.93" E