



RADIO DATA

APP	119.100
	129.850
	119.700
	119.900
	124.325
TWR	118.600
	118.850
	119.700
GND	121.800
ATIS ARR (EN)	135.075
EMERG	121.500

CHG: MAG VAR, D areas, R areas

ATC SURVEILLANCE MINIMUM ALTITUDE CHART

GENERAL INFORMATION:

A Surveillance Minimum Altitude Area (SMAA) is a defined area in which the minimum safe levels allocated by a controller giving an ATC Surveillance service for IFR flights have been predetermined.

SMAA's do not constitute controlled airspace nor do they attract any special airspace regulation in their own right.

SMAA minimum safe level ensures obstacle clearance within the area concerned plus a 3,0 NM buffer area. Minimum safe level is determined by the highest obstacle elevation or the highest terrain elevation + 60 M, whichever is higher, plus safety margin of 300 M (984 FT) rounded up to the next higher hundred feet. Number 20 shown in the SMAA symbol equals 2000 FT MSL.

This chart may only be used for cross-checking of altitudes assigned while the aircraft is identified.

COMMUNICATION FAILURE: IN ACCORDANCE WITH THE RULES OF THE AIR

Coordinates for SMAA's are listed overleaf.

EFHK ATC SURVEILLANCE MINIMUM ALTITUDE AREAS		
NAME	MIN ALT	AREA DEFINITION
EFHK SMAA S02	2200 FT	Circle, radius 3.10 NM, centre 601040N 0243824E
NAME	MIN ALT	AREA DEFINITION
EFHK SMAA S04	1800 FT	604202N 0251920E - 602855N 0254319E - 600958N 0252704E - 600318N 0250146E - 595818N 0243043E - 601107N 0240555E - 601904N 0242307E - 602612N 0242323E - 603328N 0243836E - 604202N 0251920E - Excluding EFHK SMAA S02
NAME	MIN ALT	AREA DEFINITION
EFHK SMAA S11	2100 FT	605716N 0252624E - 605453N 0253236E - 604452N 0255818E - 604321N 0260016E - 603517N 0261813E - 603237N 0261401E - 600859N 0264338E - 600800N 0263300E - 595300N 0255200E - 595430N 0252000E - 595327N 0245949E - 595300N 0245100E - 594200N 0235931E - 595447N 0234928E - 602652N 0240237E - 604433N 0242908E - 604913N 0244656E - 605659N 0250512E - 605716N 0252624E - Excluding EFHK SMAA S02 and EFHK SMAA S04