

MEMMINGEN  
RWY 06

INSTRUMENT APPROACH PROCEDURE  
TABULAR DESCRIPTION  
RNP

**Procedure Remarks**

1. PROCEDURE NOT TO BE USED DURING ACTIVITY OF NLFS.
2. EGNOS CH 67845 E06A.

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track <sup>°</sup> ) Mag Track <sup>°</sup>	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from ALG	IF	ALG	N 47 59 50.57 E 010 15 43.88	N	-	-	-	A6000+	-	-	RNP APCH	-
	TF	JA555	N 47 50 51.61 E 010 10 34.24	N	(T 201.1) 199	9.6	-	A6000+	-	-	RNP APCH	-
	TF	JA450	N 47 48 49.42 E 010 05 28.43	N	(T 239.3) 237	4.0	-	A5000+	-	-	RNP APCH	-
	TF	JA430	N 47 53 58.10 E 010 00 55.57	N	(T 329.3) 327	6.0	-	A4000+	210-	-	RNP APCH	-
	TF	FIMPE	N 47 56 00.24 E 010 06 01.10	N	(T 059.2) 057	4.0	-	A4000+	-	-	RNP APCH	-
Initial APCH from JA430	IF	JA430	N 47 53 58.10 E 010 00 55.57	N	-	-	-	A4000+	-	-	RNP APCH	-
	TF	FIMPE	N 47 56 00.24 E 010 06 01.10	N	(T 059.2) 057	4.0	-	A4000+	-	-	RNP APCH	-
APCH	TF	RW06	N 47 58 59.90 E 010 13 32.29	Y	(T 059.3) 057	5.9	-	-	-	-3.0/50	RNP APCH	-
Missed APCH	CF	JA062	N 48 01 57.01 E 010 20 59.06	Y	(T 059.4) 057	5.8	-	-	-	-	RNP APCH	-
	CA	-	-	-	(T 059.4) 057	-	-	A3100+	-	-	RNP APCH	-
	DF	ALG	N 47 59 50.57 E 010 15 43.88	N	-	-	L	@A6000	230-	-	RNP APCH	-

**RNAV HOLDING IDENTIFICATION**

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track <sup>°</sup> ) Mag Track <sup>°</sup>	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time (MIN) / Distance outbound	Turn Direction	Remarks
HM	ALG	N 47 59 50.57 E 010 15 43.88	(T 149.4) 147	230-	A6000+	1 MIN	L	-