

SID RNAV 1 RWY 35**(To be planned in case of LIN VOR unavailability only)****NOISE ABATEMENT PROCEDURES RWY 35**

See ENR 1.5 for general provisions of Civil Aviation Authority (ENAC).

ABSEM 6J

Minimum Climb Gradient: 8.0% (486 FT/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-210	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	+1150	-210	RNAV 1
DF	ABSEM	-	-	-	-	R	+4600	-210	RNAV 1

RUVAB 6J

Minimum Climb Gradient: 8% (486 FT/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-230	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	-	-230	RNAV 1
TF	ML508	-	353 (355.4)	-	4.6	-	-	-230	RNAV 1
TF	ML509	-	353 (355.4)	-	3.5	-	+5000	-230	RNAV 1
TF	RUVAB	-	054 (056.4)	-	15.7	-	+FL105	-	RNAV 1

PEPAG 1J

Minimum Climb Gradient: 9.0% (546 FT/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-250	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	-	-250	RNAV 1
TF	ML508	-	353 (355.4)	-	4.6	-	-	-250	RNAV 1
TF	ML509	-	353 (355.4)	-	3.5	-	+5600	-250	RNAV 1
TF	ML503	-	340 (343.2)	-	4.3	-	+FL85	-250	RNAV 1
TF	ML504	-	350 (352.9)	-	5.0	-	+FL105	-250	RNAV 1
TF	ML506	-	350 (352.9)	-	5.0	-	+FL135	-250	RNAV 1
TF	PEPAG	-	324 (326.5)	-	9.6	-	-	-	RNAV 1

REMARKS

- Aircraft with poor climb performance, unable to comply with the above gradients, shall advise ATC at start-up and request to be cleared on a SID towards TZO.
- SID restricted to jet aircraft.

SRN 7J

Minimum Climb Gradient: 8% (486 FT/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-230	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	-	-230	RNAV 1
TF	ML508	-	353 (355.4)	-	4.6	-	-	-230	RNAV 1
TF	ML509	-	353 (355.4)	-	3.5	-	+5000	-230	RNAV 1
TF	ML516	-	277 (280.2)	-	7.1	-	(1)	-	-
TF	SRN	-	277 (280.0)	-	3.0	-	+FL85	-	RNAV 1

REMARKS

1. MCL +90 ATC Discretion.

TOVSA 6J

Minimum Climb Gradient: 8.0% (486 FT/NM) until ABSEM.

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-210	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	+1150	-210	RNAV 1
DF	ABSEM	-	-	-	-	R	+4600	-210	RNAV 1
TF	ML624	-	156 (159.2)	-	17.2	-	-	-250	RNAV 1
TF	TOVSA	-	156 (158.6)	-	8.4	-	+6000	-	RNAV 1

TZO 7J (ATC Discretion)

Minimum Climb Gradient: 8.7% (528 FT/NM)

Path Terminator	Waypoint Identifier	Fly Over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	353 (355.7)	+2.8	-	-	+760	-230	RNAV 1
CF	ML507	Y	353 (355.7)	+2.8	-	-	-	-230	RNAV 1
TF	ML508	-	353 (355.4)	-	4.6	-	-	-230	RNAV 1
TF	TZO	-	087 (089.8)	-	10.2	R	+FL85	-	RNAV 1

WAYPOINT LIST

Waypoint Identifier	Coordinates
ML503	45°41'04.45" N 009°13'41.75" E
ML504	45°46'02.07" N 009°12'48.58" E
ML506	45°50'59.67" N 009°11'55.26" E
ML507	45°28'59.62" N 009°16'21.88" E
ML508	45°33'32.27" N 009°15'50.88" E
ML509	45°36'59.55" N 009°15'27.22" E
ML516	45°38'14.28" N 009°05'29.82" E
ML624	45°12'58.25" N 009°32'29.93" E