

RNAV TRANSITION TO ILS APPROACH via UPGAV

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	UPGAV	-	-	-	-	-	+5000 (1)	-210	-	RNAV1
020	TF	NIPLI	-	223°(226.1°)	-	6.6	-	+4000 (1)	-200	-	RNAV1
030	TF	PILUD	-	312°(315.1°)	-	2.3	R	+3000	-	-	RNAV1

RNAV TRANSITION TO ILS APPROACH via ELDIP

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	ELDIP	-	-	-	-	-	+5000 (1)	-210	-	RNAV1
020	TF	NIPLI	-	312°(315.1°)	-	5.0	-	+4000 (1)	-200	-	RNAV1
030	TF	PILUD	-	312°(315.1°)	-	2.3	-	+3000	-	-	RNAV1

RNAV TRANSITION TO ILS APPROACH via ADSAS

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	ADSAS	-	-	-	-	-	+5000 (1)	-210	-	RNAV1
020	TF	NIPLI	-	042°(045.2°)	-	6.9	-	+4000 (1)	-200	-	RNAV1
030	TF	PILUD	-	312°(315.1°)	-	2.3	L	+3000	-	-	RNAV1

REMARKS

(1) MEA 3000FT ATC Discretion