

ERFURT-WEIMAR
RWY 27

STANDARD ARRIVAL
ROUTES - INSTRUMENT (STAR)
RNAV (GPS)

NARUS ONE VICTOR											
NARUS 1V											
Procedure Remarks: CLEARANCE LIMIT NARUS.											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	NARUS	N 50 40 05.90 E 011 10 53.56	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE457	N 50 51 50.44 E 011 20 50.03	N	(T 028.2) 025	13.3	-	A5000+	-	-	RNAV 1	-
TF	DE437	N 50 56 47.70 E 011 21 52.18	N	(T 007.5) 005	5.0	-	A4000+	-	-	RNAV 1	-

RELKO ONE VICTOR											
RELKO 1V											
Procedure Remarks: CLEARANCE LIMIT RELKO.											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	RELKO	N 51 03 35.22 E 011 29 01.53	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE428	N 51 01 44.96 E 011 22 54.55	N	(T 244.6) 242	4.3	-	A5000+	-	-	RNAV 1	-
TF	DE437	N 50 56 47.70 E 011 21 52.18	N	(T 187.6) 185	5.0	-	A4000+	-	-	RNAV 1	-

ROBEL ONE VICTOR											
ROBEL 1V											
Procedure Remarks: 1. CLEARANCE LIMIT ROBEL. 2. DURING ACTIVITY OF NLFS CROSS DE424 AT OR ABOVE 7000.											
Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	ROBEL	N 50 53 51.00 E 010 26 06.18	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE424	N 50 58 03.84 E 010 39 46.26	N	(T 063.9) 061	9.6	-	-	-	-	RNAV 1	-
TF	DE423	N 51 03 45.08 E 010 58 25.41	N	(T 064.1) 061	13.1	-	-	-	-	RNAV 1	-
TF	DE425	N 51 03 00.64 E 011 07 36.59	N	(T 097.2) 094	5.8	-	-	-	-	RNAV 1	-
TF	DE426	N 51 02 29.78 E 011 13 53.99	N	(T 097.4) 095	4.0	-	-	-	-	RNAV 1	-
TF	DE428	N 51 01 44.96 E 011 22 54.55	N	(T 097.4) 095	5.7	-	A5000+	-	-	RNAV 1	-
TF	DE437	N 50 56 47.70 E 011 21 52.18	N	(T 187.6) 185	5.0	-	A4000+	-	-	RNAV 1	-

RNAV HOLDING IDENTIFICATION								
Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Speed Limit (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	NARUS	N 50 40 05.90 E 011 10 53.56	(T 007.1) 004	230-	A5000+	1 MIN	R	-
HM	RELKO	N 51 03 35.22 E 011 29 01.53	(T 235.0) 232	230-	A5000+	1 MIN	R	-
HM	ROBEL	N 50 53 51.00 E 010 26 06.18	(T 084.3) 081	230-	A5000+	1 MIN	R	-