

ENNA RNP W RWY 16 (AR) - RECOMMENDED CODING

SN	PD	WI	Fly-over	°M (°T)	MAG VAR	DIST (NM)	REC NAVAID	TD	ALT (FT)	Speed (KT)	VPA (°)/TCH (FT)	ARC CENTRE RADIUS (NM)	RNP (NM)
10	IF	ETRIG	-	-	-13	-	-	-	A4000+	-	-	-	1.0
20	TF	NA430	-	-	-13	7.5	-	-	A2700+	K220-	-	-	1.0
30	RF	NA431	-	-	-13	4.6	-	R	A1200+	-	-	NA439 2.600	0.5
40	TF	RW16	Y	-	-13	3.1	-	-	-	-	-3.4/50	-	0.3
50	TF	NA433	-	-	-13	4.0	-	-	-	K200-	-	-	1.0
60	RF	NA434	-	-	-13	6.8	-	L	-	-	-	NA438 2.000	1.0
70	TF	NEPKO	-	-	-13	16.9	-	-	-	-	-	-	1.0
80	HM	NEPKO	-	162 (175.4)	-13	1 MIN	-	R	A4000	K230-	-	-	1.0

Note: Recommended coding is based on ARINC 424 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.

Note: Published OCA(H) values are obstacle clearance values. Decision heights (DH) below 250 FT shall not be used due to approach operation Type A limitations.