

Remarks	
6	
26R	Nil
08R	Nil
26L	Nil

EDDM AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
08L	ALSAF LIH Sequence flash available	G LIH	3.0° 55.00 ft	W LIH	0–3100 m: W LIH; 3100–3700 m: R/W LIH; 3700–4000 m: R LIH. 15 m spacing	0–3400 m: W LIH; 3400–4000 m: Y LIH. 60 m spacing.	R LIH	-
26R	ALSAF LIH Sequence flash available	G LIH	3.0° 55.00 ft	W LIH	0–3100 m: W LIH; 3100–3700 m: R/W LIH; 3700–4000 m: R LIH. 15 m spacing	0–3400 m: W LIH; 3400–4000 m: Y LIH. 60 m spacing.	R LIH	-
08R	ALSAF LIH Sequence flash available	G LIH	3.0° 53.00 ft	W LIH	0–3100 m: W LIH; 3100–3700 m: R/W LIH; 3700–4000 m: R LIH. 15 m spacing	0–3400 m: W LIH; 3400–4000 m: Y LIH. 60 m spacing.	R LIH	-
26L	ALSAF LIH Sequence flash available	G LIH	3.0° 52.00 ft	W LIH	0–3100 m: W LIH; 3100–3700 m: R/W LIH; 3700–4000 m: R LIH. 15 m spacing	0–3400 m: W LIH; 3400–4000 m: Y LIH. 60 m spacing.	R LIH	-

Remarks	
10	
08L	LED lights used for the sequenced flash lights of the approach lighting system
26R	LED lights used for the sequenced flash lights of the approach lighting system
08R	LED lights used for the sequenced flash lights of the approach lighting system
26L	LED lights used for the sequenced flash lights of the approach lighting system