

ERFURT-WEIMAR  
RWY 09

STANDARD ARRIVAL  
ROUTES - INSTRUMENT (STAR)  
RNAV (GPS)

General Remarks: NOT TO BE USED DURING ACTIVITY OF NLFS.

**NARUS ONE ROMEO**

**NARUS 1R**

Procedure Remarks: CLEARANCE LIMIT NARUS.

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	NARUS	N 50 40 05.90 E 011 10 53.56	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE425	N 51 03 00.64 E 011 07 36.59	N	(T 354.8) 352	23.0	-	-	-	-	RNAV 1	-
TF	DE423	N 51 03 45.08 E 010 58 25.41	N	(T 277.3) 274	5.8	-	-	-	-	RNAV 1	-
TF	DE422	N 51 04 28.82 E 010 49 13.43	N	(T 277.2) 274	5.8	-	-	-	-	RNAV 1	-
TF	DE421	N 51 04 58.34 E 010 42 55.49	N	(T 277.1) 274	4.0	-	-	-	-	RNAV 1	-
TF	DE420	N 51 05 27.51 E 010 36 37.41	N	(T 277.0) 274	4.0	-	A5000+	-	-	RNAV 1	-
TF	DE430	N 51 00 29.85 E 010 35 39.95	N	(T 186.9) 184	5.0	-	A4000+	-	-	RNAV 1	-

**RELKO ONE ROMEO**

**RELKO 1R**

Procedure Remarks: CLEARANCE LIMIT RELKO.

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	RELKO	N 51 03 35.22 E 011 29 01.53	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE428	N 51 01 44.96 E 011 22 54.55	N	(T 244.6) 242	4.3	-	-	-	-	RNAV 1	-
TF	DE426	N 51 02 29.78 E 011 13 53.99	N	(T 277.6) 275	5.7	-	-	-	-	RNAV 1	-
TF	DE425	N 51 03 00.64 E 011 07 36.59	N	(T 277.4) 275	4.0	-	-	-	-	RNAV 1	-
TF	DE423	N 51 03 45.08 E 010 58 25.41	N	(T 277.3) 274	5.8	-	-	-	-	RNAV 1	-
TF	DE422	N 51 04 28.82 E 010 49 13.43	N	(T 277.2) 274	5.8	-	-	-	-	RNAV 1	-
TF	DE421	N 51 04 58.34 E 010 42 55.49	N	(T 277.1) 274	4.0	-	-	-	-	RNAV 1	-
TF	DE420	N 51 05 27.51 E 010 36 37.41	N	(T 277.0) 274	4.0	-	A5000+	-	-	RNAV 1	-
TF	DE430	N 51 00 29.85 E 010 35 39.95	N	(T 186.9) 184	5.0	-	A4000+	-	-	RNAV 1	-

**ROBEL ONE ROMEO**

**ROBEL 1R**

Procedure Remarks: CLEARANCE LIMIT ROBEL.

Recommended Path Terminator	Waypoint Identifier	Coordinates	Fly Over	(True Track°) MAG Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°)	NAV Specification	Remarks
IF	ROBEL	N 50 53 51.00 E 010 26 06.18	N	-	-	-	A5000+	-	-	RNAV 1	-
TF	DE450	N 50 55 32.18 E 010 34 42.70	N	(T 072.7) 070	5.7	-	A5000+	-	-	RNAV 1	-
TF	DE430	N 51 00 29.85 E 010 35 39.95	N	(T 006.9) 004	5.0	-	A4000+	-	-	RNAV 1	-

**RNAV HOLDING IDENTIFICATION**

Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) MAG Track°	Speed Limit (kt IAS)	Altitude (ft) / Flight Level	Time / Distance outbound	Turn Direction	Remarks
HM	NARUS	N 50 40 05.90 E 011 10 53.56	(T 007.1) 004	230-	A5000+	1 MIN	R	-
HM	RELKO	N 51 03 35.22 E 011 29 01.53	(T 235.0) 232	230-	A5000+	1 MIN	R	-
HM	ROBEL	N 50 53 51.00 E 010 26 06.18	(T 084.3) 081	230-	A5000+	1 MIN	R	-