

EDDK AD 2.14 Approach and runway lighting

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RWY centre line LGT LEN, spacing colour, INTST	RWY edge LGT LEN Spacing, colour INTST	RWY end LGT colour WBAR	SWY LGT LEN (M) colour
1	2	3	4	5	6	7	8	9
06	SSALR LIH	G LIH	3.0° 55.00 ft	-	Up to 1550 m: W LIH; 1550 – 2150 m: R/W LIH; 2150 m – RWY end: R LIH. 30 m spacing	Up to 1859 m: W LIH; 1859 - 2459 m: Y LIH.	R LIH	-
24	ALSAF LIH Sequence flash available	G LIH	3.0° 57.00 ft	W LIH	Up to 1550 m: W LIH; 1550 – 2150 m: R/W LIH; 2150 m – RWY end: R LIH. 30 m spacing	Up to 1859 m: W LIH; 1859 - 2459 m: Y LIH.	R LIH	-
13L	ALSAF LIH Sequence flash available	G LIH	3.0° 63.00 ft	W LIH	Up to 2900 m: W LIH; 2900 – 3500 m: R/W LIH; 3500 m – RWY end: R LIH. 15 m spacing	Up to 3215 m: W LIH; 3215 - 3815 m: Y LIH.	R LIH	-
31R	ALSAF LIH Sequence flash available	G LIH	3.0° 63.00 ft	W LIH	Up to 2900 m: W LIH; 2900 – 3500 m: R/W LIH; 3500 m – RWY end: R LIH. 15 m spacing	Up to 3215 m: W LIH; 3215 - 3815 m: Y LIH.	R LIH	-
13R	SSALR LIH	G LIH	3.0° 43.00 ft	-	Up to 900 m: W LIH; 900 – 1500 m: R/W LIH; 1500 – 1800 m: R LIH. 30 m spacing	Up to 1263 m: W LIH; 1263 - 1863 m: Y LIH.	R LIH	-
31L	SSALR LIH	G LIH	3.0° 42.00 ft	-	Up to 900 m: W LIH; 900 – 1500 m: R/W LIH; 1500 – 1800 m: R LIH. 30 m spacing	Up to 1263 m: W LIH; 1263 - 1863 m: Y LIH.	R LIH	-